

Standard for wind turbine tower elevators

ASME A17.8-2016/CSA B44.8-16

Click to view the full PDF of ASME A17.8 CSA B44.8 2016

Legal Notice for Harmonized Standard Jointly Developed by ASME and CSA Group

Intellectual property rights and ownership

As between The American Society of Mechanical Engineers ("ASME") and Canadian Standards Association (operating as "CSA Group") (collectively "ASME and CSA Group") and the users of this document (whether it be in printed or electronic form), ASME and CSA Group are the joint owners of all works contained herein that are protected by copyright, all trade-marks (except as otherwise noted to the contrary), and all inventions and trade secrets that may be contained in this document, whether or not such inventions and trade secrets are protected by patents and applications for patents. The unauthorized use, modification, copying, or disclosure of this document may violate laws that protect the intellectual property of ASME and CSA Group and may give rise to a right in ASME and CSA Group to seek legal redress for such use, modification, copying, or disclosure. ASME and CSA Group reserve all intellectual property rights in this document.

Disclaimer and exclusion of liability

This document is provided without any representations, warranties, or conditions of any kind, express or implied, including, without limitation, implied warranties or conditions concerning this document's fitness for a particular purpose or use, its merchantability, or its non-infringement of any third party's intellectual property rights. ASME and CSA Group do not warrant the accuracy, completeness, or currency of any of the information published in this document. ASME and CSA Group make no representations or warranties regarding this document's compliance with any applicable statute, rule, or regulation.

IN NO EVENT SHALL ASME AND CSA GROUP, THEIR RESPECTIVE VOLUNTEERS, MEMBERS, SUBSIDIARIES, OR AFFILIATED COMPANIES, OR THEIR EMPLOYEES, DIRECTORS, OR OFFICERS, BE LIABLE FOR ANY DIRECT, INDIRECT, OR INCIDENTAL DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES, HOWSOEVER CAUSED, INCLUDING BUT NOT LIMITED TO SPECIAL OR CONSEQUENTIAL DAMAGES, LOST REVENUE, BUSINESS INTERRUPTION, LOST OR DAMAGED DATA, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS, WHETHER BASED IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR ANY OTHER THEORY OF LIABILITY, ARISING OUT OF OR RESULTING FROM ACCESS TO OR POSSESSION OR USE OF THIS DOCUMENT, EVEN IF ASME OR CSA GROUP HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES.

In publishing and making this document available, ASME and CSA Group are not undertaking to render professional or other services for or on behalf of any person or entity or to perform any duty owed by any person or entity to another person or entity. The information in this document is directed to those who have the appropriate degree of experience to use and apply its contents, and ASME and CSA Group accept no responsibility whatsoever arising in any way from any and all use of or reliance on the information contained in this document.

ASME and CSA Group have no power, nor do they undertake, to enforce compliance with the contents of the standards or other documents they jointly publish.

Authorized use of this document

This document is being provided by ASME and CSA Group for informational and non-commercial use only. The user of this document is authorized to do only the following:

If this document is in electronic form:

- load this document onto a computer for the sole purpose of reviewing it;
- search and browse this document; and
- print this document if it is in PDF format.

Limited copies of this document in print or paper form may be distributed only to persons who are authorized by ASME and CSA Group to have such copies, and only if this Legal Notice appears on each such copy.

In addition, users may not and may not permit others to

- alter this document in any way or remove this Legal Notice from the attached standard;
- sell this document without authorization from ASME and CSA Group; or
- make an electronic copy of this document.

If you do not agree with any of the terms and conditions contained in this Legal Notice, you may not load or use this document or make any copies of the contents hereof, and if you do make such copies, you are required to destroy them immediately. Use of this document constitutes your acceptance of the terms and conditions of this Legal Notice.



Standards Update Service

ASME A17.8-2016/CSA B44.8-16 November 2016

Title: *Standard for wind turbine tower elevators*

To register for e-mail notification about any updates to this publication

- go to shop.csa.ca
- click on **CSA Update Service**

The **List ID** that you will need to register for updates to this publication is **2424602**.

If you require assistance, please e-mail techsupport@csagroup.org or call 416-747-2233.

Visit CSA Group's policy on privacy at www.csagroup.org/legal to find out how we protect your personal information.

ASMENORMDOC.COM : Click to view the full PDF of ASME A17.8 CSA B44.8 2016

ASME A17.8-2016/CSA B44.8-16
***Standard for wind turbine
tower elevators***



**CSA
Group**

®A trademark of the Canadian Standards Association and CSA America Inc., operating as "CSA Group"

Commitment for Amendments

This Code is issued jointly by The American Society of Mechanical Engineers (ASME) and the Canadian Standards Association (operating as “CSA Group”). Amendments to This Code will be made only after processing according to the Standards writing procedures of both ASME and CSA Group.

The American Society of Mechanical Engineers
(ASME)
Two Park Avenue
New York, NY 10016-5990 USA
www.asme.org

ISBN 978-0-7918-7061-7

© Copyright 2016

This international code or standard was developed under the procedures accredited as meeting the criteria for American National Standards and it is an American National Standard. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted. The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

Published in November 2016 by CSA Group
A not-for-profit private sector organization
178 Rexdale Boulevard
Toronto, Ontario, Canada M9W 1R3
www.csagroup.org

ISBN 978-1-4883-0431-6

© 2016 CSA Group

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

To purchase standards and related publications, visit our Online Store at shop.csa.ca or call toll-free 1-800-463-6727 or 416-747-4044.

Contents

ASME A17 Elevator and Escalator Standards Committee 5

CSA B44 Technical Committee on the Elevator Safety Code 7

ASME A17.8/CSA B44.8 Joint Committee on Wind Turbine Tower Elevators 12

ASME Preface 16

CSA Preface 18

1 Scope, definitions, and references 19

1.1 Scope 19

1.1.1 Effective date 19

1.2 Definitions 19

1.3 References 25

2 Wind turbine tower elevators 27

2.1 Construction of hoistways 27

2.1.1 Hoistway enclosure not required 27

2.1.2 Enclosures required at landings 27

2.1.3 Floor over travel path not required 27

2.2 Pits 27

2.3 Location and enclosing of counterweights 27

2.3.1 Counterweight runways 27

2.3.2 Access to enclosed counterweights and ropes 28

2.4 Vertical clearances for cars and counterweights 28

2.4.1 Top car clearance (maintenance/inspection access required) 28

2.4.2 Top car clearance (maintenance/inspection access not required) 28

2.4.3 Top counterweight clearance 29

2.5 Horizontal car and counterweight clearances 29

2.5.1 Between car and landing platforms 29

2.5.2 Between car and any stationary object 29

2.5.3 Between car and counterweight and counterweight guard 29

2.5.4 Measurement of clearances 29

2.6 Protection of spaces below the travel path 29

2.7 Machinery spaces, machine rooms, control spaces, and control rooms 29

2.7.1 Equipment location 29

2.8 Equipment in the travel path, machinery space, and control spaces 30

2.8.1 Electrical equipment and wiring 30

2.9 Machinery and sheave beams, supports, and foundations 30

2.9.1 Securing of machinery beams and type of supports 30

2.9.2 Loads on overhead beams and supports 30

2.9.3 Factor of safety of overhead beams and supports 30

2.9.4 Allowable stresses and deflections for machinery and sheave beams, their supports, and any support members that transmit load to the turbine tower walls 31

2.10 Guarding of equipment and standard railing 31

2.10.1	Guarding of equipment	31
2.10.2	Standard railing	31
2.10.3	Landing platform protection	32
2.11	Protection of landing platform openings	32
2.11.1	Landing platform doors or gates	32
2.11.2	Door or gate closers	32
2.11.3	Horizontal platform inside enclosure	32
2.11.4	Platform lighting	32
2.11.5	Landing platform enclosures	32
2.12	Landing platform door locking devices and electric contacts	33
2.12.1	Landing platform door and gate locking devices	33
2.12.2	Where required (for automatic call operation)	33
2.12.3	General design requirements	33
2.13	Power operation of landing platform doors and car doors or gates	34
2.14	Car enclosures, car doors and gates, and car illumination	34
2.14.1	Car enclosure	34
2.14.2	Car height	34
2.14.3	Vision panels	34
2.14.4	Enclosure panels	35
2.14.5	Strength of car top	35
2.14.6	Top of car railing	35
2.14.7	Car illumination	35
2.14.8	Emergency lighting	35
2.14.9	Car emergency exit	36
2.14.10	Car doors and gates	36
2.14.11	Car door and gate electric contacts	36
2.14.12	Clear openings	37
2.14.13	Sectioning	37
2.14.14	Ventilation	37
2.15	Car frames and platforms	37
2.15.1	Car frames and platforms	37
2.15.2	Use of cast iron	37
2.15.3	Number of compartments	37
2.15.4	Guiding means	37
2.15.5	Strength of guiding means	37
2.15.6	Car frame	38
2.15.7	Guiding members	38
2.15.8	Kickboard	38
2.15.9	Obstruction-detection devices	38
2.15.10	Warning devices	38
2.15.11	Ladder-guided platforms	39
2.16	Capacity and loading	39
2.16.1	Capacity and data plates	39
2.16.2	Information required on plates	39
2.16.3	Limitation of load, speed, and platform area	39
2.16.4	Overload detection means	39
2.16.5	Speed-limiting device	39
2.17	Car and counterweight safeties	39
2.17.1	Wire rope gripping safety	40

2.17.2	Rack-and-pinion safety	40
2.17.3	Safety marking plates	41
2.17.4	Opening of driving-machine motor and brake control circuits on safety application	41
2.17.5	Application of safety	41
2.18	Reserved for future use	41
2.19	Reserved for future use	41
2.20	Suspension means and their connections	41
2.20.1	Suspension means for counterweighted traction elevators	42
2.20.2	Suspension means for uncounterweighted traction elevators	42
2.20.3	Chains used for suspension	44
2.21	Counterweights	44
2.21.1	Counterweight guides	44
2.21.2	Types of counterweight construction	44
2.22	Buffers, bumpers, and retardations	45
2.22.1	Bumpers	45
2.22.2	Spring buffers	45
2.22.3	Retardations	45
2.23	Car and counterweight guidance systems, supports, and fastenings	45
2.23.1	Wire rope guidance system for uncounterweighted traction drive machines	45
2.23.2	Ladder guidance systems	46
2.24	Driving machines, sheaves, and brakes	47
2.24.1	Rack-and-pinion driving machines	47
2.24.2	Traction driving machines, sheave and brakes	48
2.24.3	Chain climbing machines	49
2.24.4	Material and grooving for sheaves	49
2.24.5	Factor of safety for driving machines and sheaves	50
2.24.6	Bolts transmitting torque and set screws	50
2.24.7	Friction-gearing or clutch mechanism	50
2.24.8	Use of cast iron in gears	50
2.24.9	Braking system of driving machines	50
2.24.10	Means for manual release of driving machine brake	51
2.25	Terminal stopping devices	51
2.25.1	Final terminal stopping	51
2.25.2	Normal terminal stopping	52
2.25.3	Slack rope detection	52
2.26	Operating devices and control equipment	53
2.26.1	Operation and operating devices	53
2.26.2	Electrical protective devices	53
2.26.3	Contactors and relays for use in critical operating circuits	54
2.26.4	Electrical equipment and wiring	54
2.26.5	Phase protection of motors	55
2.26.6	Installation of capacitors or other devices to make electrical protective devices ineffective	55
2.26.7	Control and operating circuits	55
2.26.8	Release and application of driving-machine brakes	56
2.27	Emergency operation and signaling devices	56
2.28	Layout drawings	57
2.29	Welding	57
2.29.1	Qualification of welders	57
2.29.2	Welding steel	57

2.29.3	Welding metals other than steel	57
2.30	Engineering tests, type tests, and certification requirements	57
2.30.1	Type tests of interlocks, combination mechanical locks, and electric contacts and door or gate electric contacts	57
2.31	Maintenance, repair, replacement, and testing	58
2.31.1	Required information	58
2.31.2	Location	58
2.31.3	Material and construction	58
2.32	Acceptance inspections and tests	58
2.33	Periodic inspections and witnessing of tests	58

Annex A (informative)	— Wind turbine tower elevator clearances	59
-----------------------	--	----

ASMENORMDOC.COM : Click to view the full PDF of ASME A17.8 CSA B44.8 2016

ASME A17 Elevator and Escalator Standards Committee

H.E. Peelle III, *Chair*

R.A. Gregory, *Vice-Chair*

C.W. Rogler, *Vice-Chair*

G.A. Burdeshaw, *Secretary*

E.V. Baker, IUEC

M.D. Morand, *Alternate*, Qualified Elevator Inspector Training Fund (QEITF)

T.D. Barkand, U.S. Department of Labor

R.E. Baxter, Baxter Residential Elevators, LLC

K.S. Lloyd Jr., *Alternate*, Abell Elevator International

L. Bialy, Louis Bialy & Associates, LLC

K.L. Brinkman, Kevin L. Brinkman & Associates

J. Brooks, Wagner Consulting Group

G.A. Burdeshaw, American Society of Mechanical Engineers (ASME)

J.W. Coaker, Coaker & Co., PC

J. Filippone, Port Authority of New York and New Jersey

K.P. Morse, *Alternate*, NAVFAC EXWC

G.W. Gibson, George W. Gibson & Associates

R.D. Shepherd, *Alternate*, NAESA International

R.A. Gregory, Consultant, Vertex Corp.

P.S. Rosenberg, *Alternate*, Performance Elevator Consulting, LLC

P. Hampton, Thyssenkrupp Elevator

R.J. Walker, *Alternate*, ThyssenKrupp Elevator

J.T. Herrity, VTE

D.A. Kalgren, KONE Inc.

D.S. Boucher, *Alternate*, KONE Inc.

J. Koshak, Elevator Safety Solutions, LLC

H. Simpkins, *Alternate*, Thyssenkrupp Elevator

R. Kremer, Technical Standards & Safety Authority

D. McColl, Otis Canada Inc.

D. McLellan, Technical Standards & Safety Authority

J.L. Meyer, National Elevator Inspection Services, Bureau Veritas

H.E. Peelle III, The Peelle Company Ltd.

S.P. Reynolds, *Alternate*, The Peelle Company Ltd.

A. Rehman, Schindler Elevator Corp.

J.W. Blain, *Alternate*, Schindler Elevator Corp.

V.P. Robibero, Schindler Elevator Corp.

J. Carlson, *Alternate*, Schindler Elevator Corp.

C.W. Rogler, Consultant

R.S. Seymour, Robert L. Seymour & Associates, Inc.

D.M. Stanlaske, Consultant

J.R. Runyan, *Alternate*, Consultant

M.H. Tevyaw, MHT Codes & Consulting

D.L. Turner, Davis L Turner & Associates, LLC

R.S. Caporale, *Alternate*, RSC Consulting

D.A. Witham, G.A.L. Manufacturing Corp.

R.C. Burch, *Alternate*, G.A.L. Manufacturing Corp.

J. Xue, *Delegate*, Shanghai Institute of Special Equipment Inspection and Technical Research

CSA B44 Technical Committee on the Elevator Safety Code

D. McColl	Otis Canada, Inc., Mississauga, Ontario <i>Category: Producer Interest</i>	<i>Chair</i>
C.M. Ayling	Ayling Consulting Services Inc. (ACSI), Mississauga, Ontario <i>Category: User/General Interest</i>	
T. Baik	Toronto Transit Commission, Toronto, Ontario	<i>Associate</i>
L. Bialy	Otis Elevator Company, Farmington, Connecticut, USA	<i>Associate</i>
S. Bornstein	KONE Elevators, Mississauga, Ontario <i>Category: Producer Interest</i>	
M. Brierley	Coldwater, Ontario	<i>Associate</i>
K.L. Brinkman	National Elevator Industry, Inc., Eureka, Illinois, USA	<i>Associate</i>
D. Brockerville	Service NL, Newfoundland and Labrador, St. John's, Newfoundland and Labrador	<i>Associate</i>
D. Bruce	Alberta Municipal Affairs, Edmonton, Alberta <i>Category: Regulatory Authority</i>	
K.C. Cheong	AES Engineering, Vancouver, British Columbia <i>Category: User/General Interest</i>	
E.A. Donoghue	Edward A. Donoghue Associates Incorporated, Salem, New York, USA	<i>Associate</i>
K. Dunbar	Government of the Northwest Territories, Yellowknife, Northwest Territories <i>Category: Regulatory Authority</i>	

D. Eastman	Service NL, Newfoundland and Labrador, St. John's, Newfoundland and Labrador <i>Category: Regulatory Authority</i>	
M. Fournier	STM (Société de transport de Montréal), Montréal, Québec <i>Category: User/General Interest</i>	
A. Ghazanchaei	Otis Canada, Inc., Mississauga, Ontario	<i>Associate</i>
G.W. Gibson	George W. Gibson & Associates Inc., Sedona, Arizona, USA	<i>Associate</i>
J. Gill	British Columbia Safety Authority (BCSA), New Westminster, British Columbia <i>Category: Regulatory Authority</i>	
P. Girouard	Plafolift Inc., Warwick, Québec	<i>Associate</i>
A. Gower	Manitoba Office of the Fire Commissioner, Winnipeg, Manitoba <i>Category: Regulatory Authority</i>	
H. Hamze	British Columbia Safety Authority (BCSA), New Westminster, British Columbia	<i>Associate</i>
R.E. Haukeness	Technical Safety Authority of Saskatchewan, Regina, Saskatchewan <i>Category: Regulatory Authority</i>	
A.S. Hopkirk	Trident Elevator Company Limited, Scarborough, Ontario <i>Category: User/General Interest</i>	
R. Isabelle	KJA Consultants Inc., Toronto, Ontario <i>Category: User/General Interest</i>	
F. Kassem	ThyssenKrupp Elevator Canada, Montréal, Québec	<i>Associate</i>

R.M. Kennedy	Nova Scotia Department of Labour and Advanced Education, Dartmouth, Nova Scotia <i>Category: Regulatory Authority</i>	
J.W. Koshak	Elevator Safety Solutions, LLC, Collierville, Tennessee, USA	<i>Associate</i>
R. Kremer	Technical Standards & Safety Authority, Toronto, Ontario <i>Category: Regulatory Authority</i>	
D. Laguerre	Schindler Elevator Corporation, Toronto, Ontario <i>Category: Producer Interest</i>	
E. MacArthur	PEI Department of Communities, Cultural Affairs and Labour, Charlottetown, Prince Edward Island <i>Category: Regulatory Authority</i>	
S.E. MacArthur	PEI Department of Communities, Cultural Affairs and Labour, Charlottetown, Prince Edward Island	<i>Associate</i>
A. Marchant	Alimak Hek Inc., Shelton, Connecticut, USA <i>Category: Producer Interest</i>	
R. Marsiglio	H. H. Angus & Associates Ltd., Toronto, Ontario <i>Category: User/General Interest</i>	
K.L. McGettigan	International Union of Elevator Constructors (IUEC), Effingham, New Hampshire, USA	<i>Associate</i>
A. McGregor	Rooney, Irving & Associates Ltd., Ottawa, Ontario	<i>Associate</i>
B.F. McIntyre	IUEC Local No. 50, Ajax, Ontario <i>Category: User/General Interest</i>	
D. McLellan	Technical Standards & Safety Authority, Toronto, Ontario	<i>Associate</i>

S. Mercier	Régie du bâtiment du Québec, Montréal, Québec <i>Category: Regulatory Authority</i>	
M. Mihai	Technical Standards & Safety Authority, Toronto, Ontario	<i>Associate</i>
M. Pedram	ThyssenKrupp Northern Elevator Corp., Scarborough, Ontario <i>Category: Producer Interest</i>	
H. Peelle	The Peelle Company Limited, Brampton, Ontario <i>Category: Producer Interest</i>	
A. Rehman	Schindler Elevator Corporation, Morristown, New Jersey, USA	<i>Associate</i>
A. Reistetter	National Elevator & Escalator Association, Mississauga, Ontario	<i>Associate</i>
S. Reynolds	The Peelle Company Limited, Brampton, Ontario	<i>Associate</i>
J. Rooney	Priestman, Neilson & Associates Ltd., Kanata, Ontario <i>Category: User/General Interest</i>	
R. Scharfe	Public Works & Government Services Canada, Ottawa, Ontario <i>Category: User/General Interest</i>	
K. Steeves	New Brunswick Department of Public Safety, Moncton, New Brunswick	<i>Associate</i>
M. Tevyaw	MHT Codes & Consulting Specialist, Burlington, Ontario	<i>Associate</i>
B. Virk	Unitech Elevator Company, Pickering, Ontario <i>Category: Producer Interest</i>	
J. Virk	Unitech Elevator Company, Pickering, Ontario	<i>Associate</i>

L. Yang	CSA Group, Toronto, Ontario	<i>Associate</i>
M. Zingarelli	MAD Elevator Fixtures Inc., Etobicoke, Ontario	<i>Associate</i>
O. Simonetta	CSA Group, Toronto, Ontario	<i>Project Manager</i>

ASMENORMDOC.COM : Click to view the full PDF of ASME A17.8 CSA B44.8 2016

ASME A17.8/CSA B44.8 Joint Committee on Wind Turbine Tower Elevators

J. Koshak	Elevator Safety Solutions, LLC, Collierville, Tennessee, USA	<i>Chair</i>
C. Vanhoutte	Sky Man USA, LLC, Chambersburg, Pennsylvania, USA	<i>Vice-Chair</i>
M. Gerson	American Society of Mechanical Engineers (ASME), New York, New York, USA	<i>Secretary</i>
A. Altholtmann	Goracon Systemtechnik GmbH, Steinfurt, Germany	
C. Barrett	Elevator Industry Work Preservation Fund, Kent, Washington, USA	
J.L. Borwey	State of Iowa, Urbandale, Iowa, USA	
G. Brickell	Power Climber, Berwick, Victoria, Australia	
G. Burdeshaw	American Society of Mechanical Engineers (ASME), New York, New York, USA	
C.E. Cuenin	Cuenin Elevator Corporation, Grand Ridge, Florida, USA	<i>Alternate</i>
E.M. Elzinga	Genie Industries, Redmond, Washington, USA	<i>Alternate</i>
S.H. Franklin	Suspended Climbing Systems Inc., Tulsa, Oklahoma, USA	
A. Freixas	Goian NA, LLC, Ankeny, Iowa, USA	
K. Govaert	Sky Man International NV, Boom, Belgium	

P.S. Grewal	Hailo LLC, Elberton, Georgia, USA
R.J. Gromek	The OXBUILT Company, Amarillo, Texas, USA
J.J. Haigh	SafeWorks, LLC, Menomonee Falls, Wisconsin, USA
J.T. Herrity	VTE, Fleming Island, Florida, USA
R.S. Hultstrom	Elevator Industry Work Preservation Fund, Columbia, Maryland, USA
R.E. Kaspersma	Liftinstituut, Wieringerwerf, Netherlands
T. Look	BP Wind Energy, Idaho Falls, Idaho, USA
A.J. Marchant	Alimak Hek Inc., Shelton, Connecticut, USA
K. Matharu	Tractel, Scarborough, Ontario, Canada
L. Metzinger	Avanti Wind Systems Inc., New Berlin, Wisconsin, USA
J. Rearick	Rearick & Company Inc., Houston, Texas, USA
P.D. Smith	Tempest Group, Grand Ridge, Florida, USA
S. Swett	SwettCorp, Houston, Texas, USA
O. Virus-Tetzlaff	Goracon Systemtechnik GmbH, Steinfurt, Germany
S.W. Weaver	Amarillo, Texas, USA

R. Weinmuller RW Innovations,
Amity Harbor, New York, USA

T. Westphal WRD Management Support GmbH,
Aurich, Germany

H. Wu Shanghai Institute of Special Equipment Inspection
and Technical Research,
Shanghai, China

O. Simonetta CSA Group,
Toronto, Ontario, Canada

Project Manager

ASMENORMDOC.COM : Click to view the full PDF of ASME A17.8 CSA B44.8 2016

ASME Foreword

Equipment covered by this standard was originally codified and incorporated into ASME A17.1-2013/CSA B44-13, Section 5.11, in October 2013. The first edition of this Code was published in November 2016 and prepared by The American Society of Mechanical Engineers (ASME), Wind Turbine Tower Elevator Committee with the assistance of representatives of a number of interests including manufacturers, certifying organizations, regulatory bodies, and technical consultants from North America and Europe.

The work to develop this Code originated when the A17 Standards Committee was presented information on the numbers of these elevators already installed and the estimate of projected number of elevators to be constructed in North America.

The A17 Standards Committee voted that these elevators were under the Scope of ASME A17.1/CSA B44, Safety Code for Elevators and Escalators and in January 2009, assigned the project of developing language to the Special Purpose Personnel Elevator (SPPE) Committee. The SPPE Committee created a Project Team consisting of A17/B44 representatives, technical advisors from the American Wind Energy Association (AWEA), specialists in the design of these types of elevators, manufacturers from Denmark, Belgium, Spain, and Canada, and two members from Accredited Elevator/Escalator Certifying Organizations (AECOs) from the Netherlands and the United States.

The first Project Team meeting was held in March 2009. A number of meetings of the Team were held during the next three years, using the Special Purpose Personnel Elevator language, Section 5.7, as a basis for developing Wind Turbine Elevator Code language. The Team performed hazard assessment to establish equivalent levels of safety considering the very unique environment these elevators are installed where current A17.1/B44 codes do not address specific circumstances and structural requirements. In 2012, the Project Team was converted to a full Working Committee of A17, and the A17.1/B44, Section 5.11 was completed, approved by ANSI, and published as an American National Standard, ASME A17.1-2013/CSA B44-13. In 2013, the A17 Standards Committee approved the conversion of Section 5.11 into ASME A17.8/CSA B44.8 to provide a global code to international manufacturers in an effort to harmonize worldwide construction, installation, operation, testing, inspection, maintenance, alteration, and repair requirements.

ASME A17.8-2016 was approved as an American National Standard by the American National Standards Institute (ANSI) on January 8, 2016.

ASME Preface

General

This Code is one of numerous codes and standards developed and published by The American Society of Mechanical Engineers (ASME) under the general auspices of the American National Standards Institute (ANSI).

CORRESPONDENCE WITH THE A17 COMMITTEE

ASME codes and standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this and other ASME A17 codes and standards may interact with the committee by requesting interpretations, proposing revisions, and attending committee meetings. Correspondence should be addressed to:

Secretary, A17 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016

All correspondence to the Committee must include the individual's name and post office address in case the Committee needs to request further information.

Proposing Revisions

Revisions are made periodically to the Code to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the procedures, and in order to conform to developments in the elevator art. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Code. Such proposals should be as specific as possible: citing the Section number(s), the proposed wording, and a detailed description of the reasons for the proposal including any pertinent documentation.

Requesting Interpretations

Upon request, the A17 Committee will render an interpretation of any requirement of the Code. Interpretations can only be rendered in response to a written request sent to the Secretary of the A17 Standards Committee at: <http://go.asme.org/Inquiry>.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his request utilizing the following format:

Subject: Cite the applicable Section number(s) and a concise description.

Edition: Cite the applicable edition and supplement of the Code for which the interpretation is being requested.

Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The question shall be phrased, where possible, to permit a specific "yes" or "no" answer. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format will be rewritten in this format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME committee or subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings

The A17 Standards Committee and the various Working Committees regularly hold meetings and/or telephone conferences all of which are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the Standards Committee. Future committee meeting dates and locations can be found on the committee page at <https://cstools.asme.org/>.

ASMENORMDOC.COM : Click to view the full PDF of ASME A17.8 CSA B44.8-2016

CSA Preface

This is the first edition of ASME A17.8/CSA B44.8, *Standard for wind turbine tower elevators*.

Originally, wind turbine tower elevators were covered in ASME A17.1-2013/CSA B44-13, Section 5.11, published in October 2013. This Code supersedes those requirements. This is a fully harmonized binational Standard.

This Code was prepared for use in Canada by the CSA Technical Committee on the Elevator Safety Code under the jurisdiction of the CSA Strategic Steering Committee on Mechanical Industrial Equipment Safety. It has been formally approved by the CSA Technical Committee.

Notes:

- 1) *Use of the singular does not exclude the plural (and vice versa) when the sense allows.*
- 2) *Although the intended primary application of this Code is stated in its Scope, it is important to note that it remains the responsibility of the users of the Code to judge its suitability for their particular purpose.*
- 3) *This publication was developed by consensus, which is defined by CSA Policy governing standardization — Code of good practice for standardization as "substantial agreement. Consensus implies much more than a simple majority, but not necessarily unanimity". It is consistent with this definition that a member may be included in the Technical Committee list and yet not be in full agreement with all clauses of this publication.*
- 4) *To submit a request for interpretation of this Code, please send the following information to inquiries@csagroup.org and include "Request for interpretation" in the subject line:*
 - a) *define the problem, making reference to the specific clause, and, where appropriate, include an illustrative sketch;*
 - b) *provide an explanation of circumstances surrounding the actual field condition; and*
 - c) *where possible, phrase the request in such a way that a specific "yes" or "no" answer will address the issue.*

Committee interpretations are processed in accordance with the CSA Directives and guidelines governing standardization and are available on the Current Standards Activities page at standardsactivities.csa.ca.

- 5) *This Code is subject to review five years from the date of publication. Suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquiries@csagroup.org and include "Proposal for change" in the subject line:*
 - a) *designation;*
 - b) *relevant clause, table, and/or figure number;*
 - c) *wording of the proposed change; and*
 - d) *rationale for the change.*
- 6) *Attention is drawn to the possibility that some of the elements of this Code may be the subject of patent rights. CSA Group is not to be held responsible for identifying any or all such patent rights. Users of this Code are expressly advised that determination of the validity of any such patent rights is entirely their own responsibility.*

ASME A17.8-2016/CSA B44.8-16

Standard for wind turbine tower elevators

1 Scope, definitions, and references

1.1 Scope

ASME A17.8/CSA B44.8 applies to elevators permanently installed in a wind turbine tower to provide vertical transportation of authorized personnel and their tools and equipment only.

Such elevators are typically subjected to extreme temperatures, humidity variations, and substantial horizontal motions where, by reason of their limited use and the types of construction of the structures served, full compliance with ASME A17.1/CSA B44 Part 2 is not practicable or necessary.

1.1.1 Effective date

The requirements of this edition and subsequent addenda to the Code are effective as of the date noted on the copyright page of this document. The AHJ will establish the effective date for its local regulations.

1.2 Definitions

The following definitions shall apply in this Code:

Authorized personnel — persons who have been instructed in the operation of the equipment and designated by the owner to use the equipment.

Brake, driving machine, elevator, dumbwaiter, or material lift — an electromechanically or electrohydraulically released spring, or gravity applied device, that is part of the electric driving machine of the elevator, dumbwaiter, or material lift used to apply a controlled force at a braking surface to hold or retard the elevator, dumbwaiter, or material lift.

Electromechanically released — a means of brake release in which an electric current applied to an actuator (such as a solenoid) causes an electromagnetic force that overcomes a resisting force (such as a spring) as long as the electric current flows.

Buffer — a device designed to stop a descending car or counterweight beyond its normal limit of travel by storing or by absorbing and dissipating the kinetic energy of the car or counterweight.

Spring buffer — a buffer utilizing one or more springs to cushion the impact force of the descending car or counterweight.

Bumper — a device other than an oil or spring buffer designed to stop a descending car or counterweight beyond its normal limit of travel by absorbing the impact.

Cable, traveling — see **Traveling cable**.

Capacity — see **Rated load**.

Car, elevator — the load-carrying unit including its platform, car frame, enclosure, and car door or gate.

Car enclosure — the top and the walls of the car resting on and attached to the car platform.

Car frame — the supporting frame to which the car platform, upper and lower sets of guide shoes, car safety, and the hoisting ropes or hoisting-rope sheaves, or the plunger or cylinder of a direct-acting elevator, are attached.

Car platform — the structure that forms the floor of the car and that directly supports the load.

Certified — see **Listed/certified**.

Certifying organization — an approved or accredited, independent organization concerned with product evaluation that maintains periodic inspection of production of listed/certified equipment or material and whose listing/certification states whether that equipment meets appropriate standards or has been tested and found suitable for use in a specified manner.

Note: For the purpose of this definition, accredited means that an organization has been evaluated and approved by an Authorized Agency to operate a Certification/Listing program, and is designated as such in a publication of the Authorized Agency.

Clearance, top car, inclined elevators — the shortest distance in the direction of travel between the upward most portion of the chassis (car frame) and the nearest obstruction when the car is level with the top terminal landing.

Clearance, top counterweight — the shortest vertical distance between any part of the counterweight structure and the nearest part of the overhead structure or any other obstruction when the car floor is level with the bottom terminal landing.

Control, motion — that portion of a control system that governs the acceleration, speed, retardation, and stopping of the moving member.

Control, operation — that portion of a control system that initiates the starting, stopping, and direction of motion in response to a signal from an operating device.

Operation, automatic — operation control wherein the starting of the elevator, dumbwaiter, or material lift car is effected in response to the momentary actuation of operating devices at the landing, and/or of operating devices in the car identified with the landings, and/or in response to an automatic starting mechanism, and wherein the car is stopped automatically at the landings.

Operation, automatic call — operation control wherein the starting of a wind turbine tower elevator car is effected in response to the momentary actuation of operating devices not mounted on the car and wherein the car is stopped automatically at the terminal landing or at the next landing in the direction of travel.

Operation, automatic send — operation control wherein the starting of a wind turbine tower elevator car is effected in response to the momentary actuation of operating devices mounted on the car and only accessible from outside the car, wherein the car is stopped automatically at the terminal landing or at the next landing in the direction of travel.

Controller — a device or group of devices that serves to control in a predetermined manner the apparatus to which it is connected.

Controller, motor — the operative units of a motion control system comprising the starter devices and power conversion equipment required to drive an electric motor.

Door — the movable portion(s) of an entrance that closes the openings. It consists of one or more solid face panels that are permitted to be equipped with a vision panel.

Door, horizontally sliding — a door that moves horizontally.

Door or gate, self-closing — a manually opened door or gate that closes when released.

Door, swinging — a door that pivots around a vertical axis.

Door or gate electric contact — an electrical device, the function of which is to prevent operation of the driving machine by the normal operating device unless the door or gate is in the closed position.

Driving machine — see **Machine, driving**.

Driving machine, traction climbing — an uncounterweighted driving machine where traction results from the weight of the car and its load.

Elevator — a hoisting and lowering mechanism, equipped with a car, that moves within guides and serves two or more landings and is classified by the following type:

Elevator, wind turbine tower — a hoisting and lowering mechanism equipped with a car installed in a wind turbine tower.

Elevator personnel — persons who have been trained in the construction, maintenance, repair, inspection, or testing of equipment.

Emergency stop switch — a device located as required and readily accessible for operation that, when manually operated, causes the electric power to be removed from the driving-machine motor and brake of an electric elevator; or from the electrically operated valves and pump motor of a hydraulic elevator; or of a dumbwaiter; or of a material lift.

Endurance limit of a component — the maximum stress that can be alternated or reversed within specified limits without producing fracture of the component material.

Engineering test — a test carried out or witnessed by a registered or licensed professional engineer, testing laboratory, or certifying organization to ensure conformance to Code requirements.

Factor of safety — the ratio of the ultimate strength to the working stress of a member under maximum static loading, unless otherwise specified in a particular requirement.

Gate — the moveable portion(s) of an entrance that closes the opening. A gate has through openings.

Governor — see **Speed governor**.

Guide rope fixes — wire guide rope attachment hardware securing the guiding system to the structure.

Hoistway (shaft), elevator, dumbwaiter, or material lift — an opening through a building or structure for the travel of elevators, dumbwaiters, or material lifts, extending from the pit floor to the roof or floor above.

Hoistway door or gate locking device — a device that secures a hoistway door or gate in the closed position and prevents it from being opened from the landing side except under certain specified conditions.

Hoistway door combination mechanical lock and electric contact — a combination mechanical and electrical device with two related, but entirely independent functions that are

- a) to prevent operation of the driving machine by the normal operating device unless the hoistway door is in the closed position
- b) to lock the hoistway door in the closed position and prevent it from being opened from the landing side unless the car is within the landing zone

Note: *As there is no positive mechanical connection between the electric contact and the door locking mechanism, this device ensures only that the door will be closed, but not necessarily locked, when the car leaves the landing. Should the lock mechanism fail to operate as intended when released by a stationary or retiring car-cam device, the door can be opened from the landing side even though the car is not at the landing. If operated by a stationary car-cam device, it does not prevent opening the door from the landing side as the car passes the floor.*

Hoistway enclosure — the fixed structure consisting of vertical walls or partitions that isolates the hoistway from all other areas or from an adjacent hoistway and in which entrances are installed.

Installation — a complete elevator, dumbwaiter, escalator, material lift, or moving walk, including its hoistway, hoistway enclosures and related construction, and all machinery and equipment necessary for its operation.

Labeled/marked — equipment or material to which has been attached a label, symbol, or other identifying mark of an approved or accredited independent certifying organization, concerned with product evaluation, that maintains periodic inspection of production of labeled/marked equipment or material, and by whose labeling/marking the manufacturer indicates compliance with appropriate standards or performance in a specified manner.

Note: *For the purpose of this definition, "accredited" means that an organization has been evaluated and approved by an Authorized Agency to operate a Certification/Listing program, and is designated as such in a publication of the Authorized Agency.*

Landing, elevator or material lift — that portion of a floor, balcony, or platform used to receive and discharge passengers or freight.

Landing, bottom terminal — the lowest landing served by the elevator or material lift that is equipped with a hoistway entrance.

Landing, top terminal — the highest landing served by the elevator or material lift that is equipped with a hoistway entrance.

Listed/certified — equipment or materials accepted for inclusion in a publication by a certifying organization.

Note: *The means for identifying listed/certified equipment may vary for each organization concerned with product evaluation, some of which do not recognize equipment as listed/certified unless it is also labeled/marked. The authority having jurisdiction utilizes the system employed by the listing/certifying organization to identify a listed/certified product.*

Load, dynamic — the load applied as a result of acceleration or deceleration.

Load, impact — a suddenly applied load.

Load, static — the load applied as a result of the weight.

Machine, driving — the power unit that applies the energy necessary to drive an elevator or other equipment covered by the scope of this Code.

Driving machine, electric — a driving machine in which the energy is applied by an electric motor. It includes the motor, driving-machine brake, and the driving sheave or drum, together with its connecting gearing, belt, or chain, if any.

Driving machine, rack-and-pinion — an electric driving machine in which the motion of the car is obtained by a power-driven rotation pinion(s) mounted on the car, traveling on a stationary rack mounted in the hoistway.

Traction machine — a direct driving machine in which the motion of a car is obtained through friction between the suspension ropes and a traction sheave.

Maintenance — a process of routine examination, lubrication, cleaning, and adjustment of parts, components, and/or subsystems for the purpose of ensuring performance in accordance with the applicable Code requirements. (See also **Repair** and **Replacement**.)

Maintenance control program (MCP) — a documented set of maintenance tasks, maintenance procedures, examinations, and tests to ensure that equipment is maintained in compliance with the requirements of ASME A17.1/CSA B44, 8.6.

Maintenance procedure — an instruction or sequence of instructions for performing a specific task(s).

Manually (manual) reset, elevator —

- a) a type or feature of an elevator part or component that, when actuated, requires intervention of a person in order to reinstate it to its nonactuated state.
- b) a type of action required to be taken by a person to reinstate an elevator part or component from an actuated state to its nonactuated state.

May — indicates permission, not a mandatory requirement.

Means, suspension — tensile components that support, raise, and lower a car, counterweight, or both.

Mechanical lock — see **Hoistway door combination mechanical lock and electric contact**.

Member, suspension — an individual load-carrying component of the suspension means (e.g., a single rope or belt).

Normal stopping means — that portion of the operation control that initiates stopping of the car in normal operation at landings.

Operating device — the car switch, push buttons, key or toggle switches, or other devices used to actuate the operation control.

Operation, inspection — a special case of continuous-pressure operation used for troubleshooting, maintenance, repair, adjustments, rescue, and inspection.

Overhead structure — all of the structural members, walls, platforms, etc., supporting the elevator machinery, sheaves, and equipment at the top of the hoistway.

Pit, elevator — the portion of a hoistway extending from the sill level of the bottom terminal landing to the floor at the bottom of the hoistway.

Platform, landing — permanent deck installed in wind turbine towers to access tower components.

Rated load, elevator, dumbwaiter, material lift, or escalator — the load that the equipment is designed and installed to lift at the rated speed.

Rated speed — the speed at which the elevator, dumbwaiter, escalator, moving walk, or material lift is designed to operate under the following conditions:

Elevator, dumbwaiter, or material lift — the speed in the up direction with rated load in the car.

Readily accessible — capable of being reached quickly for operation, renewal, or inspection without requiring those to whom ready access is a requisite to climb over or remove obstacles or resort to portable ladders, chairs, etc.

Repair — reconditioning or renewal of parts, components, and/or subsystems necessary to keep equipment in compliance with applicable Code requirements. (See also **Replacement** and **Maintenance**.)

Replacement — the substitution of a device or component and/or subsystems, in its entirety, with a unit that is basically the same as the original for the purpose of ensuring performance in accordance with applicable Code requirements. (See also **Repair** and **Maintenance**.)

Rope, suspension (hoisting) — wire rope used to raise and lower an elevator, dumbwaiter, or material lift car or its counterweight, or both.

Safety, car or counterweight — a mechanical device attached to the car, car frame, or to an auxiliary frame; or to the counterweight or counterweight frame; to stop and hold the car or counterweight under one or more of the following conditions: predetermined overspeed, free fall, or if the suspension ropes slacken.

Shaft — see **Hoistway**.

Shall — indicates a mandatory requirement.

Should — indicates a recommendation, not a mandatory requirement.

Slack-rope switch — a device that automatically causes the electric power to be removed from the elevator driving machine motor and brake when the suspension ropes of a winding drum machine become slack.

Speed governor — a continuously operating speed monitoring and detection device that, at predetermined speeds, provides signals to the controller and imparts a retarding force to activate the car or counterweight safety.

Tail line — the slack portion of the suspension member extending below the traction climbing driving machine.

Terminal landing — see **Landing, elevator or material lift**.

Terminal stopping device, final — a device that automatically causes the power to be removed from a driving machine motor and brake, or from a hydraulic machine, after the car has passed a terminal landing.

Terminal stopping device, normal — device(s) to slow down and stop an elevator, dumbwaiter, or material lift car automatically at or near a terminal landing.

Travel path — in a wind turbine tower elevator, the space defined by the projected footprint of the car, inclusive of any horizontal displacement of the car, from the bottom landing platform to the uppermost point of travel or the final limit.

Traveling cable — a cable made up of electric conductors that provides electrical connection between an elevator, dumbwaiter, material lift car, or counterweight and a fixed outlet in the hoistway or machine room.

Type test — a test carried out or witnessed by a certifying organization concerned with product evaluation and the issuing of certificates to ensure conformance to Code requirements.

1.3 References

The following is a list of publications referenced in this Code:

16 CFR Part 1201 (Sections 1201.1 and 1201.2), Safety Standard for Architectural Glazing Materials

29 CFR OSHA 1910.66 (Appendix C), Powered Platforms for Building Maintenance

Publisher: U.S. Government Publishing Office

732 N. Capitol Street, NW

Washington, DC 20401

Telephone: (202) 512-1800 / (866) 512-1800

<http://www.gpo.gov/>

AGMA 218.01 (withdrawn), Rating the Pitting Resistance and Bending Strength of Spur and Helical Involute Gear Teeth

Publisher: American Gear Manufacturers Association

1001 N Fairfax Street

Alexandria, VA 22314-1587

Telephone: (703) 684-0211

<http://www.agma.org>

ANSI Z535.2 (latest edition), Environmental and Facility Safety Signs

Publisher: American National Standards Institute

25 West 43rd Street

New York, NY 10036

Telephone: (212) 642-4900

<http://www.ansi.org>

AISC S326 (withdrawn), Specification for Design, Fabrication, and Erection of Structural Steel for Buildings

Publisher: American Institute of Steel Construction

One East Wacker Drive

Chicago, IL 60601-1802

Telephone: (312) 670-2400

<http://www.aisc.org>

ANSI/AWS D1.1 (latest edition), Structural Welding Code — Steel

ANSI/AWS D1.3 (latest edition), Structural Welding Code — Sheet Steel

Publisher: American Welding Society

8669 NW 36 Street, #130

Miami, FL 33166

Telephone: (800) 443-9353

<http://www.aws.org>

ASME A17.1/CSA B44 (2013), Safety Code for Elevators and Escalators

ASME A17.6 (latest edition), Standard for Elevator Suspension, Compensation, and Governor Systems

Publisher: The American Society of Mechanical Engineers

Two Park Avenue

New York, NY 10016

Telephone: (212) 591-8500

<http://www.asme.org>

ASTM E8/E8M (latest edition), Standard Test Methods for Tension Testing of Metallic Materials

Publisher: American Society for Testing and Materials

100 Barr Harbor Drive

P.O. Box C700

West Conshohocken, PA 19428-2959

Telephone: (610) 832-9585

<http://www.astm.org>

CAN/CGSB 12.1 (latest edition), Tempered or Laminated Safety Glass

CAN/CGSB 12.11 (latest edition), Wired Safety Glass

CAN/CGSB 12.12 (latest edition), Plastic Safety Glazing Sheets

Publisher: Canadian General Standards Board

11 Laurier Street

Gatineau, Québec K1A 1G6

Telephone: (819) 956-0425

<http://www.tpsgc-pwgsc.gc.ca/ongc-cgsb/index-eng.html>

CSA B44.1/ASME A17.5 (latest edition), Elevator and Escalator Electrical Equipment

CSA C22.1 (latest edition), Canadian Electrical Code, Part I

CSA C22.2 No. 141-15, Emergency Lighting Equipment

CAN/CSA S16.1-94 (replaced by CSA S16-14), Limit States Design of Steel Structures

CSA W47.1-09 (R2014), Certification of Companies for Fusion Welding of Steel

CSA W59-13, Welded Steel Construction (Metal Arc Welding)

CSA Z259.16 (latest edition), Design of Active Fall-Protection Systems

CAN/CSA-Z321 (withdrawn), Signs and Symbols for the Workplace

Publisher: CSA Group

178 Rexdale Boulevard

Toronto, Ontario M9W 1R3

Telephone: (416) 747-4044 / (800) 463-6727

shop.csa.ca

BS EN 12016 (latest edition), Electromagnetic compatibility — Product family standard for lifts, escalators and moving walks — Immunity

BS EN 13411-3 (latest edition), Terminations for steel wire ropes — Safety — Part 3: Ferrules and ferrule-securing

Publisher: British Standards Institution

389 Chiswick High Road

London, W4 4AL United Kingdom

Telephone: +44 020 8996 9000

<http://www.bsi-global.com>

NFPA 70 (latest edition), National Electrical Code
Publisher: National Fire Protection Association
1 Batterymarch Park
Quincy, MA 02169-7471
Telephone: (617) 770-3000
<http://www.nfpa.org>

UL 924, Emergency Lighting and Power Equipment
Publisher: Underwriters Laboratories, Inc.
333 Pfingsten Road
Northbrook, IL 60062-2096
Telephone: (847) 272-8800
<http://www.ul.com>

2 Wind turbine tower elevators

2.1 Construction of hoistways

2.1.1 Hoistway enclosure not required

Full hoistway enclosures are not required.

2.1.2 Enclosures required at landings

Partial hoistway enclosures shall be required at landing platforms and shall conform to 2.11.

2.1.3 Floor over travel path not required

A floor over the travel path is not required; however, when provided shall conform to 2.1.3.1 and 2.1.3.2.

2.1.3.1

Overhead floors shall be capable of sustaining a concentrated load of 1 000 N (225 lb) on any 2 000 mm² (3 in²) area, and in addition, where it constitutes the floor of the main or secondary level machinery space, it shall be designed for a live load not less than 6 kPa (125 lb/ft²) in all open areas.

2.1.3.2

Floors shall be of metal construction and if perforated, the openings shall reject a ball 25 mm (1 in) in diameter or be provided with a guard surrounding the perforation a minimum of 50 mm (2 in) in height.

2.2 Pits

2.2.1

Pits shall not be provided.

2.3 Location and enclosing of counterweights

2.3.1 Counterweight runways

Counterweights, where provided, shall have their runways fully enclosed and shall run in separate guides.

2.3.2 Access to enclosed counterweights and ropes

Access shall be provided for inspection, maintenance, and repair of an enclosed counterweight and its ropes. Doors or gates in the counterweight enclosures shall be self-closing and shall be provided with

- a) an electric contact, the opening of which will remove power from the elevator driving-machine motor and brake
- b) a self-locking keyed tumbler lock.

2.4 Vertical clearances for cars and counterweights

2.4.1 Top car clearance (maintenance/inspection access required)

Where access to the car top is required for maintenance or inspection and when the car has reached its maximum upward movement, the clearance above the car top, measured vertically up to the horizontal plane described by the lowest part of the overhead structure or other obstruction and measured within the projection of the car enclosure top exclusive of the area outside the standard railing (see 2.10.2), where provided, shall be not less than 1 100 mm (43 in). In no case shall the following additional clearances be less than:

- a) 600 mm (24 in) above the car crosshead assembly except when the crosshead is located over the car enclosure top or the distance which any sheave assembly mounted in or on the crosshead projects above the top of the car crosshead, whichever is greater, but in no case shall there be less than 150 mm (6 in) clearance above the sheave assembly.
- b) 300 mm (12 in) above the car crosshead assembly where the crosshead is adjacent to the car enclosure top. The crosshead shall not overlap the car enclosure top by more than 100 mm (4 in) horizontally.
- c) 600 mm (24 in) above equipment attached to and projecting above the car enclosure top, exclusive of
 - i) standard railings
 - ii) areas outside of the standard railing, the vertical clearance shall be not less than 100 mm (4 in)
 - iii) roller and sliding guide assemblies.

Where access to the car top is required for maintenance and inspection of equipment, a railing conforming to 2.10.2 within 50 mm (2 in) of the perimeter of the car enclosure top shall be provided. When the car has reached its maximum upward movement, there shall be a clearance not less than 100 mm (4 in) from the highest projection of the car top railing to the nearest part of the overhead structure.

2.4.2 Top car clearance (maintenance/inspection access not required)

Where access to the car top is not required for maintenance or inspection

- a) equipment mounted on the car top shall not strike any part of the overhead structure or the equipment located in the travel path when the car has reached its maximum upward movement, and
- b) a sign shall be provided with the words "DANGER LOW CLEARANCE"* prominently posted on the car top equipment. The sign shall conform to ANSI Z535.2 or CAN/CSA-Z321, whichever is applicable. The sign shall be of such material and construction that the letters and figures stamped, etched, cast, or otherwise applied to the face shall remain permanently legible.

* The equivalent French wording is "DANGER, JEU RÉDUIT".

2.4.3 Top counterweight clearance

Top counterweight clearance, where counterweights are provided, shall not be less than 600 mm (24 in).

2.5 Horizontal car and counterweight clearances

Clearances shall conform to 2.5.1 through 2.5.4.

2.5.1 Between car and landing platforms

The clearance between the car and the landing platform shall be greater than or equal to 25 mm (1 in) on the sides used for loading and unloading (see Nonmandatory Annex A).

2.5.2 Between car and any stationary object

There shall be a minimum of 25 mm (1 in) clearance between the car structure and any stationary objects. Clearances are permitted to be maintained by rollers or similar devices mounted on the car. Clearance shall be measured from the car structure.

2.5.3 Between car and counterweight and counterweight guard

The clearance between the car and the counterweight shall be not less than 40 mm (1.5 in) at all times and under all operating conditions. The clearance between the car and the counterweight guard, counterweight and the counterweight guard, and between the counterweight and the hoistway enclosure shall be not less than 20 mm (0.8 in).

2.5.4 Measurement of clearances

The clearances shall be measured with no load on the car platform.

2.6 Protection of spaces below the travel path

Where the travel path does not extend to the lowest floor of the structure and there is space below the travel path that is accessible, the floor shall be capable of sustaining

- a) a concentrated load of 1 kN (225 lb) on any 2 000 mm² (3 in²) area, and
- b) a live load not less than 6 kPa (125 lb/ft²) in all open areas.

2.7 Machinery spaces, machine rooms, control spaces, and control rooms

Elevator machine rooms and control rooms are not permitted in wind turbine towers.

2.7.1 Equipment location

Elevator equipment shall be located in machinery spaces and control spaces on the car or outside the travel path and shall conform to 2.7.1.1 and 2.7.1.2.

2.7.1.1 Motor controller location

The motor controller shall be

- a) located in a machinery space and control space, in an enclosure with a door(s) or panel(s) that is (are) not self-closing and that shall be kept closed
- b) readily accessible for maintenance and inspection at all times
- c) lit by permanently installed electric lighting with a lighting intensity of at least 200 lx (19 fc) at the cabinet when power is applied to the motor controller or temporary lighting with a lighting intensity of at least 200 lx (19 fc) at the cabinet when power is removed from the motor controller.

2.7.1.2 Temperature and humidity

All equipment shall be designed for the ambient air temperature and humidity range specified by the wind turbine manufacturer. The temperature and humidity range shall be permanently posted on the cabinet. The height of the letters and figures shall be not less than 3 mm (0.125 in).

2.8 Equipment in the travel path, machinery space, and control spaces

2.8.1 Electrical equipment and wiring

Installation of electrical equipment and wiring shall conform to NFPA 70 or CSA C22.1, whichever is applicable. Turbine electrical generation equipment is permitted in spaces outside the travel path provided the nonelevator equipment does not interfere with the operation of the elevator equipment.

2.9 Machinery and sheave beams, supports, and foundations

Overhead machinery beams and supports shall conform to 2.9.1 through 2.9.4.

2.9.1 Securing of machinery beams and type of supports

2.9.1.1

All machinery and sheaves shall be so supported and secured as to effectively prevent any part becoming loose or displaced.

2.9.1.2

Overhead beams directly supporting machinery shall be of steel.

2.9.1.3

Machinery or equipment shall be secured to and supported on, or from the top of, overhead beams, except for the following equipment:

- a) secondary or deflecting sheaves of traction elevators
- b) devices and their accessories for limiting or retarding car speed
- c) driving machines on the car.

2.9.1.4

Cast iron in tension shall not be used for supporting members for sheaves where they are hung beneath beams.

2.9.2 Loads on overhead beams and supports

Overhead beams, floors, and their supports shall be designed for not less than the load imposed by the guide ropes of rope-guided systems plus twice the sum of the following loads:

- a) the load secured to or supported by the beams and supports, that shall include the complete weight of the machine, sheaves, controller, governor, and any other equipment, together with that portion, if any, of the machinery space or control space supported thereon; and
- b) the sum of the tensions in all suspension members supported by the beams and their supports with rated load in the car.

Note: (2.9.2) The object in doubling the suspended load is to allow for impact, accelerating stresses, etc.

2.9.3 Factor of safety of overhead beams and supports

The factor of safety for overhead beams and their supports shall be not less than 5 for steel.

2.9.4 Allowable stresses and deflections for machinery and sheave beams, their supports, and any support members that transmit load to the turbine tower walls

2.9.4.1

The unit stresses for all machinery and sheave beams and their supports, based on the loads computed as specified in 2.9.2, tensions shall not exceed 80% of those permitted for static loads by AISC S326 or CAN/CSA-S16.1, whichever is applicable.

2.9.4.2

The allowable deflections of machinery and sheave beams, their immediate supports, and any support members loaded in bending that transmit load to guide rails or turbine tower walls under static load shall not exceed 1/1666 of the span.

2.10 Guarding of equipment and standard railing

2.10.1 Guarding of equipment

In machinery and control spaces, the following shall be guarded to protect against accidental contact:

- a) exposed sheaves and pinch points
- b) exposed gears, sprockets, and chains
- c) exposed keys, keyways, and screws in projecting shafts.

2.10.2 Standard railing

A standard railing shall be substantially constructed of metal and shall consist of a top rail, intermediate rail or equivalent structural member or solid panel, and toe-board.

2.10.2.1

The top rail shall have a smooth surface, and the upper surface shall be located at a vertical height of 1 070 mm (42 in) from the working surface.

2.10.2.2

The intermediate rail or equivalent structural member or solid panel shall be located approximately centered between the top rail and the working surface.

2.10.2.3

The toe-board shall be securely fastened and have a height not less than 100 mm (4 in) above the working surface.

2.10.2.4

A standard railing shall be capable of resisting anywhere along its length the following forces when applied separately, without deflecting more than 75 mm (3 in) and without permanent deformation:

- a) A force of at least 890 N (200 lbf) applied in any lateral or downward vertical direction at any point along the top rail.
- b) A force of at least 666 N (150 lbf) applied in any lateral or downward vertical direction at any point along the center of the intermediate rail, member, or panel. If the standard railing is a solid panel extending from the top rail to the toe-board, the application of the force specified in 2.10.2.4 a) shall be considered to meet the requirements of 2.10.2.4 b).
- c) A force of 225 N (50 lbf) applied in a lateral direction to the toe-board.

2.10.3 Landing platform protection

A standard railing protecting the openings in landing platforms shall be provided and conform to 2.11.5.

2.11 Protection of landing platform openings

Protection of landing openings shall conform to 2.11.1 through 2.11.5.

2.11.1 Landing platform doors or gates

A landing platform door or gate shall be permanently installed and shall be one of the following types:

- a) horizontally sliding
- b) horizontally swinging
- c) combination horizontally sliding and swinging.

2.11.2 Door or gate closers

Landing platform doors and gates shall be openable with not more than 50 N (11 lbf) and be self-closing or provided with a means to assure the door is closed when the car is not at a landing.

2.11.3 Horizontal platform inside enclosure

The horizontal distance between the travel path side of the door or gate and the edge of the landing platform shall be less than or equal to 65 mm (2.5 in) (see Nonmandatory Annex A).

2.11.4 Platform lighting

The landing platform shall be so lighted that the illumination, when the elevator is in service, shall be not less than 27 lx (2.5 fc) at the standing surface.

2.11.5 Landing platform enclosures

Where the travel path is adjacent to areas accessible by authorized or elevator personnel, the landing platform enclosure shall conform to 2.11.5.1 through 2.11.5.7.

2.11.5.1

It shall be enclosed to a height not less than 1 070 mm (42 in) above the floor or stair treads with a standard railing (see 2.10.2).

2.11.5.2

It shall be at the bottom landing and have a solid or openwork enclosure that rejects a ball 25 mm (1 in) in diameter.

2.11.5.3

It shall be of sufficient strength to prevent contact between the enclosure and the car or counterweight when the enclosure is subjected to a force of

- a) 890 N (200 lbf) applied within 50 mm (2 in) of the top edge, and
- b) 1 112 N (250 lbf) applied at right angles at any point over an area of 100 mm × 100 mm (4 in × 4 in).

2.11.5.4

It shall have a horizontal clearance not less than 90 mm (3.5 in) and no more than 150 mm (6 in) between loading side of the car and inside of landing platform enclosure (see Nonmandatory Annex A).

2.11.5.5

It shall be provided with a means of entrance to the car complying with [2.11.2](#).

2.11.5.6

Landing platform horizontally sliding doors and gates shall have means provided to prevent the hangers from jumping the track and stops provided in the assembly to prevent hangers from overrunning the end of the track.

2.11.5.7

The hoistway face or hardware of the landing platform doors or gates shall not project into the travel path beyond the edge of the landing platform.

2.12 Landing platform door locking devices and electric contacts

2.12.1 Landing platform door and gate locking devices

Landing platform door mechanical lock and electric contacts are not required except where automatic call operation is provided.

2.12.2 Where required (for automatic call operation)

Where required by [2.26.1.2 c](#)), landing platform door mechanical lock and electric contacts shall be provided and conform to [2.12.3](#).

2.12.3 General design requirements

Combination mechanical locks and electric contacts shall conform to [2.12.3.1](#) through [2.12.3.5](#).

2.12.3.1

They shall be so designed that the locking member and the electric contact are mounted on and attached to a common base in such a manner that there is a fixed relation between the location of the contact and the location of the locking member.

They shall be so installed and adjusted that the electric contact cannot close until the door is in the closed position and so that the locking member is in a position to lock the door when or before the contact closes. In order to prevent motion of the door from opening the electric contact while the door is locked in the closed position, multiple-locking points shall, where necessary, be provided on the locking mechanism.

2.12.3.2

The electric contact shall be positively opened by the locking bar of the mechanical lock or by a lever or other device attached to and operated by the door, and the electric contact shall be maintained in the open position by the action of gravity or by a restrained compression spring, or both, or by positive mechanical means.

2.12.3.3

The mechanical lock shall hold the door in the locked position by means of gravity or by a restrained compression spring, or both.

2.12.3.4

Mercury tube switches shall not be used.

2.12.3.5 Listing/certification door locking devices and door or gate electric contacts

2.12.3.5.1 Type tests

Each type and make of landing platform door combination mechanical lock and electric contact shall conform to the type tests specified in ASME A17.1/CSA B44, 8.3.3. The tests shall be done by or under the supervision of a certifying organization.

2.12.3.5.2 Listing/certification

Each type and make of landing platform door combination mechanical lock and electric contact shall conform to the general requirements for tests and certification specified in ASME A17.1/CSA B44, 8.3.1.

2.12.3.5.3 Identification marking

Each listed/certified device shall be labeled. It shall be permanently attached to the device and shall be so located as to be readily visible when the device is installed in its operating position.

The label shall include the following data:

- a) the name, trademark, or certifying organization file number by which the organization that manufactured the product can be identified
- b) the certifying organization name or identifying symbol
- c) statement of compliance with ASME A17.1 or CSA B44
- d) a distinctive type, model, or style letter or number
- e) rated voltage and current, and whether AC or DC
- f) rated test force and rated test movement when the device is of a type released by an actuating device mounted on the car when tested per ASME A17.1/CSA B44, 8.3.3.4.7, except the term “retiring cam” shall be replaced with words “actuating device mounted on the car”
- g) date (month and year) devices subjected to type test specified in [2.12.3.5.1](#)
- h) if the device has only been type tested and listed/certified for use on a wind turbine tower elevator, the label shall indicate the restricted use.

2.13 Power operation of landing platform doors and car doors or gates

Power operation of landing platform doors and car doors or gates is prohibited.

2.14 Car enclosures, car doors and gates, and car illumination

2.14.1 Car enclosure

Cars shall be enclosed with metal at the sides and top. The enclosure walls shall be designed to reject a 25 mm (1 in) ball up to a height of 2 135 mm (84 in).

2.14.2 Car height

The minimum clear height inside the car shall be no less than 2 000 mm (78 in). The clear height shall be permitted to be reduced to 1 930 mm (76 in) provided all projections below 2 000 mm (78 in) are marked with yellow and black diagonal stripes not less than 25 mm (1 in) in width.

2.14.3 Vision panels

Vision panels are permitted in the enclosure walls provided they are located 1 000 mm (39 in) above the floor.

2.14.4 Enclosure panels

Where enclosures include panels of glass, or transparent or translucent plastic, the panels shall

- a) be constructed of laminated glass that complies with the requirements of 16 CFR Part 1201, Sections 1201.1 and 1201.2; or be constructed of laminated glass, safety glass, or safety plastic that complies with CAN/CGSB-12.1, CAN/CGSB-12.11, or CAN/CGSB-12.12, whichever is applicable
- b) be mounted in the structure so that the assembly shall withstand the required elevator tests without damage
- c) have markings as specified in the applicable glazing standard that shall be on each separate piece, and shall remain visible after installation.

2.14.5 Strength of car top

The car enclosure top shall be so designed and installed as to be capable of sustaining a load of 135 kg (300 lb) on any area 600 mm × 600 mm (24 in × 24 in), or 45 kg (100 lb) applied to any point, without permanent deformation. The resulting deflection under these loads shall be limited to prevent damage to any equipment, devices, or lighting assemblies fastened to or adjacent to the car enclosure top.

2.14.6 Top of car railing

Where the car top is intended to be used for operation of the car for maintenance or inspection, it shall be provided with a car top standard railing conforming to 2.10.2.

2.14.7 Car illumination

Illumination in the car shall be provided from a permanent light source inside or outside the car. The light source shall provide illumination of at least 27 lx (2.5 fc) at the floor of the car platform with car door or gate in the closed position.

2.14.8 Emergency lighting

Illumination in the car shall be provided from an emergency light source in the car or from outside the car. The light source shall provide a minimum level of illumination of 2 lx (0.2 fc), measured at any point between 890 mm (35 in) and 1 225 mm (48 in) above the car floor and approximately 300 mm (12 in) centered horizontally in front of a car.

2.14.8.1

Emergency lights shall be automatically turned on when normal car lighting power fails.

2.14.8.2

The power system shall be capable of maintaining the minimum light intensity specified for a period of at least 30 min.

2.14.8.3

Not less than two lamps of approximately equal wattage shall be used.

2.14.8.4

Battery-operated units mounted on the car, where provided, shall

- a) conform to CSA C22.2 No. 141 or UL 924
- b) be permanently connected to a car light circuit provided from the elevator controller.

2.14.9 Car emergency exit

Means for emergency exit from the car shall be provided and shall conform to 2.14.9.1 and either 2.14.9.2 or 2.14.9.3.

2.14.9.1

Rated personnel protective equipment anchorage point(s), appropriate to the number of persons the car is designed to carry, shall be provided for safe emergency exit conforming to 29 CFR OSHA 1910.66 (Appendix C) or CSA Z259.16.

2.14.9.2

Emergency exit through the car door or gate is permitted where the distance from the point of emergency exit to the accessible means of evacuation does not exceed 1 100 mm (43 in).

2.14.9.3

Access through the top or bottom of a ladder-guided car is permitted where

- the distance from the point of access to the accessible means of evacuation is equal to or less than 1 100 mm (43 in) and the exit,
- the opening has an area not less than 227 000 mm² (352 in²), and shall not measure less than 380 mm (15 in) on any side,
- be so located as to provide a clear passageway, unobstructed by fixed elevator equipment located in or on top of the car,
- the access covers are hinged, or otherwise attached, to the car and open in the upward direction only, and
- the access cover(s) is (are) equipped with a switch or contact that, when opened, removes power from the driving-machine motor and brake.

2.14.10 Car doors and gates

Each car shall be equipped with a car door or gate conforming to the following:

- when closed, guard the opening to its full height,
- be mechanically prevented from unintentional opening,
- be openable from inside the car and from outside the car at any point in the travel path,
- be of solid or openwork construction that will reject a ball 25 mm (1 in) in diameter,
- when made of materials other than metal, conform to 2.14.3 and 2.14.4,
- not be power operated, and
- when subjected to a force of 335 N (75 lbf) applied on an area 300 mm (12 in) square at right angles to and approximately at the center of the door or gate, doors and gates shall not be permanently deformed or be displaced from their guides or tracks.

2.14.11 Car door and gate electric contacts

Each car door or gate shall be provided with a door or gate electric contact conforming to the following:

- it shall remove power from the driving-machine motor and brake when the car door or gate is not in the closed position,
- it shall be positively opened by a device attached to and operated by the door or gate,
- it shall be maintained in the open position by the action of gravity or by a restrained compression spring, or both, or by positive mechanical means, and
- it shall not utilize mercury tube switches.

2.14.11.1

Each type and make of car door or gate electric contact shall be type tested per 2.30. The tests shall be done by or under the supervision of a certifying organization.

2.14.11.2

Each listed/certified device shall be labeled. It shall be permanently attached to the device, and shall be so located as to be readily visible when the device is installed in its operating position. The label shall include the following data:

- a) the name, trademark, or certifying organization file number by which the organization that manufactured the product can be identified
- b) the certifying organization name or identifying symbol
- c) a distinctive type, model, or style letter or number
- d) rated voltage and current, and whether AC or DC.

2.14.12 Clear openings

The clear opening of the car door or gate shall be a minimum of 450 mm (18 in) wide.

2.14.13 Sectioning

Car doors or gates are permitted to be sectioned provided each section partially covering the car enclosure entrance conforms to 2.14.1 through 2.14.14. The lower door section shall be a minimum of 1 100 mm (43 in) in height.

2.14.14 Ventilation

Natural ventilation openings shall be provided in the car enclosures with a total area of not less than 3.5% of the inside car floor area divided equally between the bottom and top of the car enclosure.

2.15 Car frames and platforms

Car frames and platforms shall conform to 2.15.1 through 2.15.11.

2.15.1 Car frames and platforms

Car frames and car platforms shall be metal.

2.15.2 Use of cast iron

Cast iron shall not be used in the construction of any member of the car frame or platform other than for guide shoes and guide-shoe brackets.

2.15.3 Number of compartments

The car shall not have more than one compartment.

2.15.4 Guiding means

Car frames shall be guided on each side by upper and lower guiding members attached to the frame.

2.15.5 Strength of guiding means

Guiding members shall be designed to withstand the forces imposed during normal operation of the elevator, emergency stopping, and the application of safeties.

2.15.6 Car frame

All structural components of the car frames and platforms shall have a minimum factor of safety of 5.

2.15.7 Guiding members

Failure of any guiding member shall not permit the car and car frame to strike any portion of the tower structure. Obstruction-detection devices (see 2.15.9) shall be permitted to detect when the car is outside the travel path.

2.15.8 Kickboard

The car platform shall be provided with a kickboard with a minimum of 25 mm (1 in) and a maximum of 100 mm (4 in) in height, located on the side used for loading and unloading and shall be marked yellow.

2.15.9 Obstruction-detection devices

The top and bottom of the car shall be provided with a means to detect an obstruction in the travel path and stop the car by causing the power to be removed from the driving-machine motor and brake. Each obstruction-detection device shall

- a) be provided with a switch actuated by the obstruction-detection device whose contacts are positively opened mechanically; their opening shall not be solely dependent on springs,
- b) be designed in such a manner that it cannot be reset until the obstruction-detection mechanism has been returned to the unapplied position,
- c) be designed to withstand the forces imposed on it,
- d) have a maximum actuation force of 70 N (15 lbf) and a throw not to exceed 100 mm (4 in). The switch shall actuate upon movement of the obstruction-detection device,
- e) detect a ball greater than 100 mm (4 in) in diameter within the projected area of the car, and
- f) not permit restarting of the elevator when an obstruction device resets, after being actuated.

2.15.10 Warning devices

Cars shall be provided with an external visual warning device or an audible warning device (or both) that operates while the car is in motion.

2.15.10.1

The illumination of the external visual warning device shall be a minimum of 500 lx (46 fc) measured at a point 2.5 m (8 ft) from the horizontal surfaces of the car with a flash frequency between 50 to 80 times per minute and be visible above and below the car.

2.15.10.2

The audible warning device shall have a minimum sound level of 70 dBA at 1 000 mm (39 in) in the travel path and below the elevator, with a 50% duty cycle and a frequency between 1 kHz and 4 kHz and be audible above and below the car.

2.15.10.3

Means shall be provided to assure operation of the visual or audible warning device during primary power loss for a minimum of 30 min. If a battery is used for this purpose, testing, replacement, and inspection procedures shall be provided in the MCP (see ASME A17.1/CSA B44, 8.6.1.2).

2.15.11 Ladder-guided platforms

Platforms for ladder-guided systems are permitted to have perforations or be of fabricated openwork construction. Openings shall reject a ball 10 mm (3/8 in) in diameter.

2.16 Capacity and loading

2.16.1 Capacity and data plates

Every car shall be provided with a capacity plate and a data plate permanently and securely attached. The capacity plate shall be located in a conspicuous position inside the car.

2.16.2 Information required on plates

2.16.2.1 Capacity plates

Capacity plates shall be marked in a legible and permanent manner with letters and figures not less than 25 mm (1 in) in height indicating the rated load of the elevator in kilograms or pounds, or both.

2.16.2.2 Data plates

Data plates shall be marked in a legible and permanent manner with letters and figures not less than 3 mm (0.125 in) in height indicating

- the weight of the complete car, including the driving machine and all auxiliary equipment attached to the car,
- the rated load and speed,
- the suspension-means data required,
- the name or trademark of the manufacturer and year manufactured, and
- guiding means lubrication instructions.

2.16.3 Limitation of load, speed, and platform area

The rated load shall not exceed 454 kg (1 000 lb). The inside net platform area shall not exceed 1.2 m² (13 ft²). The minimum rated load shall not be less than that based on 3.4 kPa (70 lbf/ft²) of inside net platform area or 113 kg (250 lb), whichever is greater. The rated speed shall not exceed 0.4 m/s (80 ft/min).

2.16.4 Overload detection means

A means to detect an overload shall be provided and the overload value determined by the manufacturer's recommendations. A visual or audible signal device shall be provided so that authorized personnel are notified of an overload condition.

2.16.5 Speed-limiting device

A means shall be provided to limit the descent speed of the car to less than safety tripping speed when the manual brake release system is operated.

2.17 Car and counterweight safeties

Each car, and where required by 2.6 each counterweight, shall be provided with a safety conforming to 2.17.1 or 2.17.2 and the applicable requirements of 2.17.3 through 2.17.5.

2.17.1 Wire rope gripping safety

The safety shall be operated without delay by the breakage of the suspension means or by the action of an internal centrifugal governor when the car exceeds rated speed up to a maximum of 0.9 m/s (175 ft/min).

2.17.1.1

The safety shall act on an independent safety wire rope upon loss of suspension or overspeed (see 2.20.2.8).

2.17.1.2

Safeties shall be applied mechanically. Electric, hydraulic, or pneumatic devices shall not be used to apply the safeties or to hold such safeties in the retracted position.

2.17.1.3

When car safeties are applied, no motion of the car in the down direction shall release the safeties, but such safeties shall be permitted to be released by the motion of the car in the up direction.

2.17.1.4

Safeties shall be so designed that, on their application, the forces that provide the stopping action shall be compressive forces and shall not cause permanent deformation of the safety wire rope upon whose dimensional stability the stopping capability of the safeties is dependent.

2.17.1.5

The safety shall be located where it is readily accessible and it cannot be struck by any moving object in normal operation or under conditions of overtravel.

2.17.1.6

The minimum factors of safety and stresses of safety parts and rope connections shall not be less than 3.5, and the materials used shall have an elongation not less than 15% in a length of 50 mm (2 in) when tested in accordance with ASTM E8. Forged, cast, or welded parts shall be stress relieved.

2.17.1.7

Springs are permitted in the operation of car or counterweight safeties. Where used, and where partially loaded prior to safety operation, the loading on the spring shall not produce a fibre stress exceeding one-half the elastic limit of the material. During operation of the safety, the fibre stress shall not exceed 85% of the elastic limit of the material. Helical springs, where used, shall be in compression.

2.17.1.8

The factors of safety shall be based on the maximum stresses developed in the parts during the operation of the safety when stopping rated load from overspeed.

2.17.2 Rack-and-pinion safety

Where a single rack-and-pinion drive machine is used, the car shall be provided with one or more safeties conforming to 2.17.1 or a safety consisting of a freely rotating safety pinion, a governor, and a clamping device that shall be permitted to form an integral unit mounted on the car.

2.17.2.1

The safety shall operate without delay when the car exceeds rated speed up to a maximum of 0.9 m/s (175 ft/min) bringing the car to a gradual stop on the vertical rack.

2.17.2.2

Where multiple rack-and-pinion driving machines are provided, a safety is not required when

- a) each driving machine is independently able to prevent a car that is loaded to 125% of rated load from descending uncontrolled,
- b) each driving machine is capable of moving the car to the bottom floor under manual control, and
- c) the failure of one driving machine is detected and power is removed from the other driving-machine motor and brake.

2.17.2.3

The stopping distance of the car measured from the time the safety or alternate means actuates to a full stop shall be a minimum of 25 mm (1 in) and a maximum of 380 mm (15 in).

2.17.3 Safety marking plates

Marking plates shall be metal and be securely attached or adjacent to each safety so as to be readily visible, and shall be marked in a legible and permanent manner with letters and figures not less than 3 mm (0.125 in) in height indicating

- a) the type of safety, based on 2.17,
- b) the maximum tripping speed in m/s (ft/min) for which the safety is permitted,
- c) the maximum weight in kg (lb) that the safety is designed and installed to stop and sustain,
- d) the manufacturer's name or trademark,
- e) the year of manufacture, and
- f) the force in N (lbf) required to activate the safety if applicable.

2.17.4 Opening of driving-machine motor and brake control circuits on safety application

Safeties shall be provided with a switch that opens (actuates) causing the power to be removed from the driving-machine motor and brake at the time the safety actuates and shall be of a type that cannot be reset until the safety mechanism has been returned to the unapplied position and conforms to 2.26.2.3.

2.17.5 Application of safety

A safety device that depends on the completion or maintenance of an electric circuit for the application of the safety is not permitted. Safeties shall be applied mechanically.

2.18 Reserved for future use

2.19 Reserved for future use

2.20 Suspension means and their connections

Suspension means shall conform to ASME A17.6, and 2.20.1 through 2.20.3, as applicable. Access for suspension-means inspection purposes shall be provided.

2.20.1 Suspension means for counterweighted traction elevators

For counterweighted traction elevators, suspension means shall be galvanized and conform to ASME A17.6 Part 1, and 2.20.1.1 through 2.20.1.5 for steel wire rope.

2.20.1.1

The minimum diameter of any steel wire rope shall be not less than 9.5 mm (0.375 in).

2.20.1.2

The factor of safety of the steel wire rope shall not be less than 7.95.

2.20.1.3

The arc of contact of a steel wire rope on a traction sheave and the shape of the grooves shall be sufficient to produce adequate traction under all load conditions.

2.20.1.4

No car or counterweight steel wire rope shall be lengthened or repaired by splicing. If one rope of a set is worn or damaged and requires replacement, the entire set of ropes shall be replaced.

2.20.1.5

The car or counterweight ends of steel wire ropes shall be fastened by properly attached fittings as recommended by wire-rope manufacturers.

2.20.2 Suspension means for uncounterweighted traction elevators

For uncounterweighted traction elevators, the suspension members shall be galvanized preformed steel wire rope and conform to ASME A17.6 Part 1, and 2.20.2.1 through 2.20.2.4 for steel wire rope.

2.20.2.1

The minimum diameter of any suspension steel wire rope shall not be less than 8 mm (0.3125 in).

2.20.2.2

The factor of safety of the suspension means shall be not less than 10. The factor of safety shall be calculated by the following formula:

$$F = \frac{(S \times N)}{W}$$

where

N = number of runs of suspension members under load

S = manufacturer's rated breaking force in kN (lbf) of one suspension member

W = maximum static load in kN (lbf) imposed on all suspension members with the car and its rated load at any position in the hoistway

2.20.2.3

The arc of contact of a steel wire rope on a traction sheave and the shape of the groove shall be sufficient to produce adequate traction under all load conditions.

2.20.2.4

No car suspension rope shall be lengthened or repaired by splicing.

2.20.2.5

Suspension steel wire rope terminated at the upper end shall be fastened by properly attached fittings as recommended by wire-rope manufacturers or by swage fittings complying with the following:

- a) Use of swage fittings only on regular lay, synthetic core, or IWRC ropes are permitted.
- b) They are swaged in a shop with a press under controlled conditions to guarantee reliable attachment.
- c) Where rope adjustment is required, it may only be used at one end of the rope.
- d) Swages shall be designed and tested in accordance with the design and testing requirements of BS EN 13411-3.
- e) The swaging company shall be identified on the swage or on the rope data tag.
- f) Swaging shall not be performed in the field.
- g) The manufacturer shall provide verification means to assure the swage is crimped to manufacturer's specification.

2.20.2.6

U-bolt type rope clamps or similar devices shall not be used on the load side of suspension rope or safety wire rope fastenings.

2.20.2.7

Fastenings shall develop a minimum of at least 80% of the rope manufacturer's rated breaking force.

2.20.2.8

Means shall be provided to prevent the fastenings from having any physical contact resulting in wear of the rope or its fastening.

2.20.2.9

Use of a single suspension steel wire rope is permitted when a galvanized safety steel wire rope of equivalent size and grade as the suspension steel wire rope is provided (see 2.20.2.10).

2.20.2.10

- a) Suspension members' replacement criteria shall conform to ASME A17.6. Other manufacturers' recommended criteria shall be included in the maintenance control program (see ASME A17.1/CSA B44, 8.6.1), with sufficient detail to ensure that inspection criterion is provided.
- b) When the steel wire suspension rope is replaced, the safety steel wire rope shall also be replaced.
- c) A readily visible hour meter shall be provided on all suspended elevator cars and the suspension steel wire ropes shall be replaced after 250 h of operation or after 5 years, whichever occurs first.

2.20.2.11

A safety rope shall be provided and used only in the event of loss of primary suspension or overspeed safety actuation and shall

- a) consist of a steel wire rope upon which a safety device (see 2.17.1) actuates to stop the car, and
- b) conform to 2.20.2, except 2.20.2.3.

2.20.2.12

Only steel wire ropes in ASME A17.6 are permitted to be used in wind turbine tower elevators.

2.20.2.13

Pertinent data located on the suspension means and safety rope shall be provided by a data tag securely attached to the fastenings or adjacent to the controller. The following data shall be provided:

- a) type of suspension
- b) the diameter of the rope in millimeters or inches
- c) the suspension-means manufacturer's minimum breaking force in kN or lbf
- d) the grade of material used
- e) construction classification
- f) for steel wire rope, nonpreformed, if applicable
- g) for steel wire rope, finish coating, if applicable
- h) name or trademark of the rope manufacturer
- i) name of person or organization who installed the ropes
- j) the month and year the ropes were installed
- k) lubrication information
- l) swaging company, if applicable.

2.20.3 Chains used for suspension

Reserved for future use.

2.21 Counterweights

Counterweights, where provided, shall conform to the following.

2.21.1 Counterweight guides

Counterweights shall be guided to prevent any horizontal movement that would inhibit proper operation or cause counterweight to move from designated travel path and shall not be of sufficient weight to cause undue slackening of the hoisting ropes during acceleration or retardation of the car.

2.21.2 Types of counterweight construction

2.21.2.1

One-piece solid or laminated steel counterweights shall be permitted.

2.21.2.2

Where counterweight sections are used, means shall be provided to retain the sections in place if they become broken, whether carried in a frame or not. If tie rods are used, the sections shall be fastened together by a minimum of two tie rods that pass through all weight sections. Tie rods shall be provided with locknuts and cotter pins at each end.

2.21.2.3

The frame members and their connections shall be designed with a factor of safety not less than 5 with the elevator at rest and the counterweight at the top of its travel.

2.21.2.4

The counterweight frame shall be designed with a factor of safety not less than 2.5 at bumper or buffer engagement or safety application if provided.

2.22 Buffers, bumpers, and retardations

Cars and counterweights shall be provided with bumpers conforming to 2.22.1 or spring buffers conforming to 2.22.2.

2.22.1 Bumpers

Bumpers shall conform to the following:

- they shall be located so as to retard the car and counterweight without exceeding allowable design stresses in the car frame and counterweight frame,
- they shall be made of wood or other suitably resilient material of sufficient strength to withstand without failure the impact of the car with rated load, or the counterweight, descending at overspeed where provided, and
- the material used shall be of a type that will resist deterioration or be so treated as to resist deterioration.

2.22.2 Spring buffers

Spring buffers shall conform to the following:

- the stroke of the buffer spring shall be equal to or greater 38 mm (1.5 in)
- the buffer shall be capable of supporting, without being compressed solid or to a fixed stop, a static load having a minimum of two times the total weight of the car and its rated load for car buffers and the total weight of the counterweight for counterweight buffers
- the buffer shall be compressed solid or to a fixed stop with a static load of three times the weight of the car and its rated load for car buffers and the counterweight for total weight of the counterweight buffers
- the buffer shall be provided with a marking plate showing its load rating and stroke; markings shall be made in a permanent and legible manner.

2.22.3 Retardations

Bumpers and buffers shall develop an average retardation not in excess of 9.81 m/s^2 (32.2 ft/s^2), and shall develop no peak retardation greater than 19.6 m/s^2 (64.4 ft/s^2), having a duration exceeding 0.04 s with any load in the car.

2.23 Car and counterweight guidance systems, supports, and fastenings

Means shall be provided to assure hazards due to relative movement between the tower ladder and elevator are provided. Guiding systems shall consist of one of the following:

- wire-rope-guided conforming to 2.23.1
- ladder-guided conforming to 2.23.2.

2.23.1 Wire rope guidance system for uncounterweighted traction drive machines

2.23.1.1

Guide ropes shall be galvanized steel wire rope conforming to ASME A17.6.

2.23.1.2

Guide ropes shall be tensioned with an applied load to maintain a minimum horizontal clearance of 25 mm (1 in) from the cab enclosure to other structures in the tower at all times. A means shall be provided to indicate the minimum and maximum allowable tension in the guide ropes.

2.23.1.3

Guide ropes shall have a minimum factor of safety of 8.

2.23.1.4

Guide ropes shall be a minimum of 8 mm (0.3125 in) in diameter.

2.23.1.5

Guide rope fixes shall

- a) have a spacing no greater than 30 m (98 ft) apart,
- b) be attached at each landing platform,
- c) be capable of resisting the forces imposed without permanent deformation,
- d) maintain alignment of the wire guide rope throughout the life cycle of the elevator, and
- e) allow for axial movement.

2.23.1.6

- a) Upper terminal guide rope fastenings shall conform to [2.20.2.5](#).
- b) Lower terminal guide rope fastenings shall
 - i) be provided with a fixed termination that retains the applied load with a factor of safety of 3
 - ii) have a means to retension the rope
 - iii) be permanently anchored.

2.23.1.7

Wire guide rope systems shall be designed to be permanently installed and extend beyond the travel path of the car such that no equipment on the car shall strike wire guide systems terminal fastenings.

2.23.1.8

A minimum of two guide ropes shall be provided.

2.23.1.9

Guide ropes shall be replaced according to the replacement criteria of ASME A17.6 and replacement ropes shall be new steel wire rope of the same type and grade.

2.23.1.10

Reuse of guide ropes as suspension or safety ropes is prohibited.

2.23.1.11

Guide ropes shall be positioned to prevent uncontrolled rotation of the car.

2.23.2 Ladder guidance systems

Ladder guidance systems shall conform to [2.23.2.1](#) through [2.23.2.8](#).

2.23.2.1

Ladder guidance systems shall be of steel or aluminum. Steel shall have an elongation not less than 20% in a length of 50 mm (2 in) and aluminum shall have an elongation not less than 12% in a length of 50 mm (2 in).

2.23.2.2

Ladder guidance systems and their brackets, rail clips, fishplates, and their fastenings to the support structure shall provide a minimum factor of safety of 4 for steel and 5 for all other metals for all applicable loads.

2.23.2.3

Guide surfaces shall be securely fastened to the ladder, and the ladder guides shall not exceed a design deflection of $L/160$ of span and the combined deflection shall not deflect more than 12 mm (0.5 in) under normal operation, and shall have their joints well-fitted and strongly secured. Guide surfaces and their joints and fastenings shall withstand without failure the application of the car safety when stopping the car with its rated load.

2.23.2.4

Guide surfaces shall extend from the bottom of the travel path to a sufficient height above the top landing to prevent the guide shoes from running off the guide surfaces when the car is at its extreme upper position.

2.23.2.5

A means of visually monitoring the travel path of the car shall be provided from the point of manual lowering actuation means.

2.23.2.6

Emergency evacuation shall be provided through top and bottom hatches except when the elevator is guided on the nonclimbing side of the ladder and when the door opening is perpendicular to the ladder rungs.

2.23.2.7

The car shall maintain a minimum of 175 mm (7 in) clearance from the ladder rung when the travel path is on the nonclimbing side.

2.23.2.8

A sign with letters 25 mm (1 in) in height complying with ANSI Z535.2 or CAN/CSA-Z321 shall be posted at each ladder access point saying "**CAUTION:** Elevator is guided on this ladder; beware of moving equipment."*

* The equivalent French wording is "**AVERTISSEMENT :** Ascenseur ou monte-charge guidé sur cette échelle ; attention au matériel en mouvement."

2.24 Driving machines, sheaves, and brakes

Driving machines shall be of the traction, traction climbing, rack-and-pinion, or chain climbing drive type and shall conform to 2.24.1, 2.24.2, or 2.24.3 and the applicable requirements of 2.24.4 through 2.24.9. The installation of belt-drive, winding drum, and screw drive machines are prohibited.

2.24.1 Rack-and-pinion driving machines

Rack and-pinion machines shall conform to 2.24.1.1 through 2.24.1.9.