

INTERNATIONAL STANDARD

IEC
60335-2-5

1992

AMENDMENT 2
1999-11

Amendment 2

**Safety of household and similar electrical
appliances –**

**Part 2-5:
Particular requirements for dishwashers**

Amendement 2

Sécurité des appareils électrodomestiques et analogues –

*Partie 2-5:
Règles particulières pour les lave-vaisselle*

IECNORM.COM : Click to View the full PDF & IEC 60335-2-5:1992/AMD2:1999

© IEC 1999 — Copyright - all rights reserved

International Electrotechnical Commission
Telefax: +41 22 919 0300

3, rue de Varembé Geneva, Switzerland
e-mail: inmail@iec.ch
IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

C

For price, see current catalogue

FOREWORD

This amendment has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61/1643/FDIS	61/1739/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

A bilingual version of this amendment may be issued at a later date.

CONTENTS

Replace the title of clause 8 by:

Protection against access to live parts

7 Marking and instructions

7.12.1 Add the following:

The instructions shall state that the appliance is to be connected to the water mains using new hose-sets and that old hose-sets should not be reused.

NOTE This instruction is not required if the hoses are permanently attached to the appliance.

8 Protection against accessibility to live parts

Replace the title by:

Protection against access to live parts

22 Construction

22.6 Add the following:

Drops of undiluted rinsing agent, as specified in annex AA, are applied to the external surface of the parts from which rinsing agent could leak if a seal fails.

After the test, there shall be no rinsing agent on the insulation of internal wiring, if deterioration of the insulation could result in a hazard.

NOTE 2 The influence of opening and closing the door is taken into account.

NOTE 3 Leakage of rinsing agent onto porous material is taken into account if this material is in contact with internal wiring.

23 Internal wiring

23.3 *In the second paragraph, replace "30 000" by "100 000".*

Add:

Addition:

After the test, not more than 10 % of the strands of any conductor of the internal wiring between the main part of the appliance and the door shall be broken.

24 Components

Add:

24.101 *Addition:*

Thermal cut-outs which are necessary for compliance with 19.4 shall be non self-resetting.

Compliance is checked by inspection.

IECNORM.COM : Click to view the full PDF of IEC 60335-2-5:1992/AMD2:1999