

INTERNATIONAL STANDARD



**Radio-frequency connectors –
Part 35: Sectional specification for 2,92 series RF connectors**

IECNORM.COM : Click to view the full PDF of IEC 61169-35:2011



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

IECNORM.COM : Click to view the full PDF of IEC 61169-25:2011



IEC 61169-35

Edition 1.0 2011-07

INTERNATIONAL STANDARD



**Radio-frequency connectors –
Part 35: Sectional specification for 2,92 series RF connectors**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

T

ICS 33.120.30

ISBN 978-2-88912-559-3

CONTENTS

| | |
|---|----|
| FOREWORD..... | 4 |
| 1 Scope..... | 6 |
| 2 Normative references | 6 |
| 3 Mating face and gauge information | 6 |
| 3.1 Dimensions – High performance connectors – Grade 1 | 6 |
| 3.1.1 Connector with pin-centre contact..... | 6 |
| 3.1.2 Connector with socket-centre contact | 8 |
| 3.2 Gauges | 9 |
| 3.2.1 Gauge pins for socket-centre contact..... | 9 |
| 3.2.2 Test procedure | 9 |
| 3.3 Dimensions – standard test connectors – Grade 0..... | 10 |
| 3.3.1 Connector with pin-centre contact..... | 10 |
| 3.3.2 Connector with socket-centre contact | 11 |
| 4 Quality assessment procedure..... | 11 |
| 4.1 General..... | 11 |
| 4.2 Rating and characteristics (see Clause 6 of IEC 61169-1) | 12 |
| 4.3 Test schedule and inspection requirements – Acceptance tests..... | 14 |
| 4.3.1 Acceptance tests | 14 |
| 4.3.2 Periodic tests | 15 |
| 4.4 Procedures..... | 16 |
| 4.4.1 Quality conformance inspection..... | 16 |
| 4.4.2 Qualification approval and its maintenance..... | 16 |
| 5 Instructions for preparation of detail specifications | 17 |
| 5.1 General..... | 17 |
| 5.2 Identification of the detail specification | 17 |
| 5.3 Identification of the component..... | 17 |
| 5.4 Performance..... | 17 |
| 5.5 Marking, ordering information and related matters | 18 |
| 5.6 Selection of tests, test conditions and severities..... | 18 |
| 5.7 Blank detail specification pro forma for 2,92 series connectors..... | 19 |
| Bibliography..... | 24 |
| Figure 1 – Connector with pin-centre contact (for dimensions and notes, see Table 1)..... | 7 |
| Figure 2 – Connector with socket-centre contact (for dimensions and notes, see Table 2) | 8 |
| Figure 3 – Gauge pins for socket-centre contact (for dimensions and notes, see Table 3) | 9 |
| Figure 4 – Connector with pin-centre contact (for dimensions and notes, see Table 4)..... | 10 |
| Figure 5 – Connector with socket-centre contact (for dimensions and notes, see Table 5) | 11 |

| | |
|--|----|
| Table 1 – Dimensions of connector with pin-centre contact | 7 |
| Table 2 – Dimensions of connector with socket-centre contact..... | 8 |
| Table 3 – Dimensions of gauge pins for socket-centre contact | 9 |
| Table 4 – Dimensions of connector with pin-centre contact | 10 |
| Table 5 – Dimensions of connector with socket-centre contact..... | 11 |
| Table 6 – Rating and characteristics | 12 |
| Table 7 – Acceptance tests | 14 |
| Table 8 – Periodic tests | 15 |

IECNORM.COM : Click to view the full PDF of IEC 61169-35:2011

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RADIO-FREQUENCY CONNECTORS –**Part 35: Sectional specification for 2,92 series RF connectors**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61169-35 has been prepared by subcommittee 46F: RF and microwave passive components, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This first edition cancels and replaces IEC/PAS 61169-35, published in 2009, of which it constitutes a minor revision. The only change is that the PAS has been changed into an International Standard.

The text of this standard is based on the following documents:

| | |
|--------------|------------------|
| FDIS | Report on voting |
| 46F/191/FDIS | 46F/196/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61169 series, under the general title: *Radio-frequency connectors* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

IECNORM.COM : Click to view the full PDF of IEC 61169-35:2011

RADIO-FREQUENCY CONNECTORS –

Part 35: Sectional specification for 2,92 series RF connectors

1 Scope

This sectional specification provides information and rules for preparation of detail specification of 2,92 series RF coaxial connectors together with the pro-forma blank detail specification.

It also prescribes mating face dimensions for high performance connectors - grade 1, dimensional detail of standard test connectors - Grade 0, gauging information and tests selected from IEC 61169-1 applicable to all detail specifications relating to 2,92 series RF coaxial connectors.

This specification indicates recommended performance characteristics to be considered when writing a detail specification and it covers test schedules and inspection requirements for assessment levels M and H.

The 2,92 series coaxial connectors with characteristic impedance $50\ \Omega$, 2,92 mm inner diameter of outer conductor and screw coupling, are used for millimeter wave applications, connecting with RF cables or microstrips. The operating frequency limit is up to 40 GHz.

Mating interface standards of the 2,92 series connectors are similar to IEEE std 287-2007 (2,92 mm) and MIL-std-348A (SMK). The 2,92 connectors can be inter-mated with SMA, and 3,5 mm connectors as per following standards. SMA: IEC 61169-35, MIL-PRF-39012D and MIL-STD-348A. 3,5 mm: IEC 60169-23, IEEE std 287-2007.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies, For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61169-1:1992, *Radio-frequency connectors – Part 1: Generic specification – General requirements and measuring methods*¹

Amendment 1 (1996)

Amendment 2 (1997)

3 Mating face and gauge information


3.1 Dimensions – High performance connectors – Grade 1

3.1.1 Connector with pin-centre contact

Inch dimensions are original dimensions.

All undimensioned pictorial configurations are for reference purpose only.

¹ There exists a consolidated edition 1.2 (1998) that comprises IEC 61169-1:1992, its Amendment 1:1996 and its Amendment 2:1997.




IEC 1393/11

Figure 1 – Connector with pin-centre contact
(for dimensions and notes, see Table 1)

Table 1 – Dimensions of connector with pin-centre contact

| Ref. | mm | | in | |
|---|-------|-------|--------|--------|
| | Min. | Max. | Min. | Max. |
| <i>a</i> | 6,48 | 6,73 | 0,255 | 0,256 |
| <i>b</i> | 4,521 | 4,592 | 0,1780 | 0,1808 |
| <i>c</i> | 2,90 | 2,95 | 0,114 | 0,116 |
| <i>d</i> | 2,36 | 3,56 | 0,0929 | 0,1401 |
| <i>e</i> | 3,43 | 4,01 | 0,1351 | 0,1579 |
| <i>f</i> | 0,38 | 1,14 | 0,015 | 0,045 |
| <i>g</i> | 0,906 | 0,922 | 0,0357 | 0,0363 |
| <i>h</i> | 1,02 | 1,12 | 0,040 | 0,044 |
| <i>j</i> | 0,02 | 0,13 | 0,0008 | 0,0051 |
| <i>k</i> | 0,20 | 0,30 | 0,008 | 0,012 |
| <i>l</i> | 56° | 64° | 56° | 64° |
| NOTE 1 Mechanical and electrical reference plane. | | | | |
| NOTE 2 Nut fully forward. | | | | |
| NOTE 3 Diameter is chosen to obtain a normal impedance of 50 Ω. | | | | |
| NOTE 4 Hexagon, width across two sides is 7,85 mm to 8,00 mm (0,309 in to 0,315 in), length of the plane is 3,18 mm (0,125 in) min. | | | | |

3.1.2 Connector with socket-centre contact



IEC 1394/11

**Figure 2 – Connector with socket-centre contact
(for dimensions and notes, see Table 2)**

Table 2 – Dimensions of connector with socket-centre contact

| Ref. | mm | | in | |
|----------|------|------|--------|--------|
| | Min. | Max. | Min. | Max. |
| a | 5,28 | 5,46 | 0,208 | 0,215 |
| b | 4,60 | 4,65 | 0,181 | 0,183 |
| c | 2,90 | 2,95 | 0,114 | 0,116 |
| d | 1,88 | 1,98 | 0,074 | 0,078 |
| e | 0,02 | 0,13 | 0,0008 | 0,0051 |
| f | 0,38 | 1,14 | 0,015 | 0,045 |
| g | 5,54 | — | 0,218 | — |
| h | 2,65 | — | 0,104 | — |

NOTE 1 Mechanical and electrical reference plane.

NOTE 2 Diameter is chosen to obtain a normal impedance of 50 Ω.

NOTE 3 Design for root cut to be allowed. Chamfer not to be allowed.

NOTE 4 Design of centre contact is optional, but should meet electrical and mechanical performance requirements when mating with Ø 0,906 mm to Ø 0,922 mm (Ø 0,0357 in ~ Ø 0,0363 in) gauge pin.

3.2 Gauges

3.2.1 Gauge pins for socket-centre contact




Figure 3 – Gauge pins for socket-centre contact
(for dimensions and notes, see Table 3)

Table 3 – Dimensions of gauge pins for socket-centre contact

| Gauge A | | | | | Gauge B | | | |
|---|--------|--------|--------|--------|---|--------|--------|--------|
| Maximum material for sizing purposes | | | | | Minimum material for measurement of retention force | | | |
| | | | | | Mass of gauge: 40 g ± 1 g | | | |
| Ref. | mm | | in | | mm | | in | |
| | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. |
| <i>a</i> | 0,9360 | 0,9385 | 0,0369 | 0,0370 | 0,917 | 0,9195 | 0,0361 | 0,0362 |
| <i>b</i> | 0,76 | 1,14 | 0,0299 | 0,0449 | 1,27 | 1,90 | 0,0500 | 0,0748 |
| Material: steel, polished, surface roughness: Ra=0,4 µm (16 µin) maximum. | | | | | | | | |


3.2.2 Test procedure

The gauge A shall be inserted into the socket-centre contact one time with a minimum depth of 0,76 mm (0,0299 in). This is a sizing operation and should only be carried out when the socket-centre contact is removed from the connector.

After this, the gauge B shall be inserted into socket-centre contact. The contact shall retain the mass of the gauge in a vertical downward position.

3.3 Dimensions – standard test connectors – Grade 0

3.3.1 Connector with pin-centre contact



IEC 1396/11

Figure 4 – Connector with pin-centre contact
(for dimensions and notes, see Table 4)

Table 4 – Dimensions of connector with pin-centre contact

| Ref. | mm | | in | |
|---|-------|-------|--------|--------|
| | Min. | Max. | Min. | Max. |
| a | 6,38 | 6,73 | 0,251 | 0,256 |
| b | 4,547 | 4,577 | 0,179 | 0,1802 |
| c | 2,91 | 2,93 | 0,1145 | 0,1153 |
| d | 2,36 | 3,56 | 0,0929 | 0,1401 |
| e | 3,43 | 4,01 | 0,1351 | 0,1579 |
| f | 0,38 | 1,14 | 0,015 | 0,045 |
| g | 0,906 | 0,922 | 0,0357 | 0,0363 |
| h | 1,02 | 1,12 | 0,040 | 0,044 |
| j | 0,02 | 0,076 | 0,0008 | 0,003 |
| k | 0,20 | 0,30 | 0,008 | 0,012 |
| l | 56° | 64° | 56° | 64° |
| NOTE 1 Mechanical and electrical reference plane, surface roughness: Ra = 0,4 µm (16 µin) maximum. | | | | |
| NOTE 2 Nut fully forward. | | | | |
| NOTE 3 Hexagon, width across two sides is 7,85 mm to 8,00 mm (0,309 in to 0,315 in), length of the plane is 3,18 mm (0,125 in) min. | | | | |
| NOTE 4 Diameter is chosen to obtain a normal impedance of 50 Ω ± 0,5 Ω. | | | | |

3.3.2 Connector with socket-centre contact




Figure 5 – Connector with socket-centre contact
(for dimensions and notes, see Table 5)

Table 5 – Dimensions of connector with socket-centre contact

| Ref. | mm | | in | |
|----------|------|-------|--------|--------|
| | Min. | Max. | Min. | Max. |
| a | 5,28 | 5,46 | 0,208 | 0,215 |
| b | 4,60 | 4,63 | 0,181 | 0,1822 |
| c | 2,91 | 2,93 | 0,1145 | 0,1153 |
| d | 1,88 | 1,98 | 0,074 | 0,078 |
| e | 0,02 | 0,076 | 0,0008 | 0,003 |
| f | 0,38 | 1,14 | 0,015 | 0,045 |
| g | 5,54 | — | 0,218 | — |
| h | 2,65 | — | 0,104 | — |

NOTE 1 Mechanical and electrical reference plane, surface roughness: $R_a = 0,4 \mu\text{m}$ ($16 \mu\text{in}$) maximum,

NOTE 2 Diameter is chosen to obtain a normal impedance of $50 \Omega \pm 0,5 \Omega$,

NOTE 3 Design for root cut to be allowed, chamfer not to be allowed.

NOTE 4 Design of centre contact is optional, but should meet electrical and mechanical performance requirements, when mating with $\varnothing 0,906 \text{ mm}$ to $\varnothing 0,922 \text{ mm}$ ($\varnothing 0,0360 \text{ in}$ to $\varnothing 0,0368 \text{ in}$) gauge pin.

4 Quality assessment procedure

4.1 General

The following subclauses provide recommended rating, performance and test conditions to be considered when writing a detail specification. They also provide an appropriate schedule of tests with minimum levels of conformance inspection sampling, together with the pro forma blank detail specification (BDS) and instructions for the preparation of a detail specification.

4.2 Rating and characteristics (see Clause 6 of IEC 61169-1)

The values indicated below are recommended for 2,92 series RF connectors and are given for the writer of the detail specification. They are applicable for the condition when the connectors are fully mated.

Certain tests are listed without any recommended values being given. These tests will usually not be required. When these tests are required, appropriate values shall be entered in the detail specification at the discretion of the specification writer.

Table 6 – Rating and characteristics

| Rating and characteristics | IEC 61169-1 Subclause | Values | Remarks, deviations from standard test method |
|--|-----------------------|--|---|
| Electrical | | | |
| Nominal impedance | | 50 Ω | |
| Frequency range Grade 1 connectors | | DC~ 40 GHz | Or upper frequency limit of cable |
| Reflection factor ^a General connectors - straight styles - right-angle styles - component mounting styles - solder bucket and PCB mounting styles | 9.2.1 | DC~18 GHz: 0,0501 max. 18 GHz to 26,5 GHz 0,0631 max 26,5 GHz to 40 GHz 0,1259 max. See DS See DS See DS | |
| Centre contact resistance ^b - initial - after conditioning | 9.2.3 | $\leq 3,0 \text{ m}\Omega$ $\leq 4,0 \text{ m}\Omega$ | |
| Outer conductor continuity ^b - initial - after conditioning | 9.2.3 | $\leq 2,0 \text{ m}\Omega$ $\leq 3,0 \text{ m}\Omega$ | |
| Insulation resistance - initial - after conditioning | 9.2.5 | $\geq 5\,000 \text{ M}\Omega$ $\geq 200 \text{ M}\Omega$ | |
| Proof voltage at sea-level ^{c,d} - uncabled styles - semi-rigid 0,118 in diameter - semi-rigid and semi-flexible 0,086 in diameter - semi-rigid and semi-flexible 0,047 in diameter | 9.2.6 | 750 V 750 V 750 V 500 V | |
| Proof voltage at 4,4 kPa ^{c,d} - uncabled styles - semi-rigid 0,118 in diameter - semi-rigid and semi-flexible 0,086 in diameter - semi-rigid and semi-flexible 0,047 in diameter | 9.2.6 | 150 V 150 V 150 V 100 V | 4,4 kPa approximately equivalent to 20 km |

| Rating and characteristics | IEC 61169-1 Subclause | Values | Remarks, deviations from standard test method |
|---|-------------------------------------|--|--|
| Environmental test voltage at sea level ^{c,d} - uncabled styles - semi-rigid 0,118 in diameter - semi-rigid and semi-flexible 0,086 in diameter - semi-rigid and semi-flexible 0,047 in diameter | 9.2.6 | 250 V 250 V 250 V 175 V | |
| Environmental test voltage at 4,4 kPa ^{c,d} - uncabled styles - semi-rigid 0,118 in diameter - semi-rigid and semi-flexible 0,086 in diameter - semi-rigid and semi-flexible 0,047 in diameter | 9.2.6 | 65 V 65 V 65 V 45 V | 4,4 kPa approximately equivalent to 20 km |
| Screening effectiveness (straight cables only) ^g | 9.2.8 | ≥ 100 dB at 1 GHz | |
| Discharge test (corona effect) | 9.2.9 | See DS | Extinction voltage |
| Mechanical | | | |
| Gauge retention force (resilient contacts) - centre | 9.3.4 | ≥ 0,4 N | |
| Centre contact captivation - axial force - torque | 9.3.5 | 20 N 0,01 N•m min | Maximum displacement 0,076 mm in each direction |
| Engagement and separation - coupling nut friction | 9.3.6 | ≤ 0,23 N•m | Can be carried out by hand |
| Coupling torque - standard torque - Nm-proof torque | 9.3.6 | 0,8 ~ 1,1 N•m 1,69 N•m | |
| Technical tests on cable fixing - cable rotation (nutation) - cable pulling - cable bending - cable torsion | 9.3.7.2 9.3.8 9.3.9 9.3.10 | See DS See DS See DS See DS | |
| Tensile strength of coupling mechanism | 9.3.11 | ≥ 100 N | |
| Bending torque | 9.3.12 | Na ^f | |
| Vibration | 9.3.3 | 150 m/s ² 10~2 000 Hz | 15 g _n |
| Shock | 9.3.14 | 500 m/s ² 1/2 sine wave 11 ms | 50 g _n |
| Environmental | | | |
| Climatic category | 9.4.2 | A:40/085/21 B:55/125/21 | |
| Sealing non-hermetic | 9.4.5.1 | ≤ 100 kPa•cm ³ /h | 100 kPa to 110 kPa differential |
| Hermetic | 9.4.5.2 | ≤ 10 ⁻³ Pa•cm ³ /s | 100 kPa to 110 kPa differential |
| Salt mist | 9.4.6 | 48 h spray | |

4.3 Test schedule and inspection requirements – Acceptance tests

Table 7 – Acceptance tests

| | Test method IEC 61169-1 subclause | Assessment level M (higher) | | | | Assessment level H (lower) | | | |
|---|---|-----------------------------|-----|----------|--------|----------------------------|-----|----------|--------|
| | | Test required | IL | AQL % | Period | Test required | IL | AQL % | Period |
| Group A1 | | | | | Lot | | | | Lot |
| Visual examination | 9.1.2 | a | II | 1,0 | | a | S-3 | 1,5 | |
| Group B1 | | | | | | | | | |
| Outline dimension | 9.1.3.1 | a | S-4 | 0,40 | | a | S-3 | 4,0 | |
| Mechanical compatibility | 9.1.3.3 | a | II | 1,0 | | a | S-3 | 1,5 | |
| Engagement and separation | 9.3.6 | a | S-4 | 0,40 | | a | S-3 | 1,5 | |
| Gauge retention (resilient contacts) | 9.3.4 | ia | II | 1,0 | | ia | S-3 | 1,5 | |
| Sealing | | | | | | | | | |
| non-hermetic | 9.4.5.1 | ia | II | 0,65 | | ia | S-3 | 1,0 | |
| hermetic | 9.4.5.2 | ia | II | 0,015 | | ia | S-3 | 0,025 | |
| Voltage proof | 9.2.6 | a | II | 0,40 | Lot | a | II | 4,0 | Lot |
| Solderability (d) | 9.3.2.1.1 | ia | S-4 | 0,40 | | ia | S-3 | 4,0 | |
| Insulation resistance | 9.2.5 | a | S-4 | 0,40 | | a | S-3 | 4,0 | |

For the symbols, abbreviations and procedures, see the end of Table 8.

4.3.2 Periodic tests

There are no group C tests for levels H and M.

Table 8 – Periodic tests

| | Test method IEC 61169-1 subclause | Assessment level M (higher) | | | | Assessment level H (lower) | | | |
|---------------------------------------|--|-----------------------------|---------------------|---|---------|----------------------------|---------------------|---|---------|
| | | Test required | Number of specimens | Permitted failures per group ^a | Period | Test required | Number of specimens | Permitted failures per group ^a | Period |
| Group D1 (d) | | | 6 | 1 | 3 years | | 3 | 1 | 3 years |
| Solderability | 9.3.2.1.1 | ia | | | | ia | | | |
| - connector assemblies | | | | | | | | | |
| Resistance to soldering heat | 9.3.2.1.2 | ia | | | | ia | | | |
| Mechanical tests on cable fixing | | | | | | | | | |
| - cable rotation (nutation) | 9.3.7.2 | ia | | | | ia | | | |
| - cable pulling | 9.3.8 | ia | | | | | | | |
| - cable bending | 9.3.9 | | | | | | | | |
| - cable torsion | 9.3.10 | ia | | | | | | | |
| Bending moment | 9.3.12 | ia | | | | ia | | | |
| Strength of coupling mechanism | 9.3.11 | a | | | | a | | | |
| Group D2 (d) | | | 6 | 1 | 3 years | | 3 | 1 | 3 years |
| Contact resistance | 9.2.3 | a | | | | a | | | |
| Outer conductor and screen continuity | 9.2.3 | | | | | | | | |
| Centre conductor continuity | 9.2.3 | a | | | | a | | | |
| Vibration | 9.3.3 | a | | | | a | | | |
| Shock | 9.3.14 | a | | | | | | | |
| Damp heat, steady state | 9.4.3 | | | | | | | | |
| Salt mist | 9.4.6 | a | | | | | | | |
| Group D3 | | | ^b | 1 | 3 years | | ^b | 1 | 3 years |
| Dimensions piece part and materials | 9.1.3.2 | a | | | | a | | | |
| Group D4 (d) | | | 6 | 1 | 3 years | | 3 | 1 | 3 years |
| Mechanical endurance | 9.5 | a | | | | a | | | |
| High temperature endurance | 9.6 | a | | | | a | | | |
| Sulphur dioxide | 9.4.8 | | | | | | | | |

| | Test method IEC 61169-1 subclause | Assessment level M (higher) | | | | Assessment level H (lower) | | | |
|--|--|-----------------------------|---------------------|---|---------|----------------------------|---------------------|---|---------|
| | | Test required | Number of specimens | Permitted failures per group ^a | Period | Test required | Number of specimens | Permitted failures per group ^a | Period |
| Group D5 (d) Reflection factor Screening effectiveness Water immersion | 9.2.1 9.2.8 9.2.7 | ia ia | 6 | 1 | 3 years | ia ia | 3 | 1 | 3 years |
| Group D6 (d) Contact captivation Discharge test (corona effect) Rapid change of temperature Climatic sequence | 9.3.5 9.2.9 9.4.4 9.4.2 | ia a a a | 6 | 1 | 3 years | ia a a | 3 | 1 | 3 years |
| Group D7 (d) Resistance to solvents and contamination fluids | 9.7 | | 1 ^c | 1 | 3 years | | 1 ^c | 1 | 3 years |
| ABBREVIATIONS: a - applicable na - not applicable ia - test required (if technically applicable) (d) - destructive test -specimens shall not be returned to stock IL - inspection level AQL-acceptable quality level | | | | | | | | | |
| ^a For qualification approval, a total of 2 failures only permitted for level H and 1 failure only permitted for level M from groups D1 to D7. ^b One set of piece parts each style and variant unless using common piece parts. ^c Group D7 - number of pairs for each solvent. | | | | | | | | | |

4.4 Procedures

4.4.1 Quality conformance inspection

This shall consist of test groups A1 and B1 on a lot-by-lot basis and test groups D1 to D7 on a periodic basis.

4.4.2 Qualification approval and its maintenance

This still consists of three consecutive lots passing test groups A1 and B1 followed by selection of specimens from the lots as appropriate. These specimens shall successfully pass the specified periodic D tests.

5 Instructions for preparation of detail specifications

5.1 General

Detail specifications (DS) writer shall use the appropriate blank detail specification (BDS) proforma. The following pages comprise the BDS dedicated for use with type 2,92 connectors. As such, it will already have entered on it information relating to:

- a) the basic specification number applicable to all the detail specifications covering connector styles of the type covered by the sectional specification;
- b) the connector series designation.

The specification writer should enter the details relating to the connector style to be covered as indicated. The numbers in brackets in the BDS correspond to the following indications which shall be given.

5.2 Identification of the detail specification

- (1) The name of the National authorized institution (NAI) under whose authority the DS is published and, if applicable, the organization from whom the DS is available.
- (2) The number allocated to the DS by the relevant National authorized institution immediately preceded by the ISO two letter national identity code or "XX" when the DS is produced by an IEC technical subcommittee.
- (3) The number and issue number of the IEC/IECQ generic specification and, when applicable, the sectional specification with the national reference if different.
- (4) If different from the IEC/IECQ number, any national number of the DS, date of issue and any further information required by the national system, together with any amendment numbers.

5.3 Identification of the component

- (5) Enter the following details:
 - Style: the style designation of the connector including type of fixing and sealing, if applicable.
 - Attachment: by deletion of the inapplicable options of cable/wire: given for centre and outer conductors.
 - Special features and marking: as applicable.
 - Series designation: in bold characters/digits approximately 15 mm high.
- (6) Enter detail of assessment level and the climatic category.
- (7) A reproduction of the outline drawing and details of the panel piercing, if applicable. It shall provide the maximum envelope dimensions, also the position of the reference plane and, in the case of a fixed connector, the position of the mounting plane(s) relative to the front face of the connector.

Any maximum panel thickness limitations for fixed connectors shall be stated.
- (8) Particulars of all variants covered by the DS. As appropriate, the information shall include
 - cable type (or sizes) applicable to each variant.
 - alternative plated or protective finishes.
 - details of alternative mounting flanges having either tapped or plain mounting holes.
 - details of alternative solder spills or solder buckets including, when applicable, those for use with microwave integrated circuit (MIC) components.

5.4 Performance

- (9) Performance data listing the most important characteristics of the connector in accordance with the requirements of the relevant sectional specification. Deviations from the minimum requirements shall be clearly indicated. Not applicable shall be marked "na".

5.5 Marking, ordering information and related matters

- (10) Insert marking and ordering information as appropriate, together with details of related documents and any invoked structural similarity.

5.6 Selection of tests, test conditions and severities

- (11) 'na' shall be used to indicate non-applicable tests. All tests marked 'a' by the detail specification writer shall be mandatory.

When using the normal procedure with a dedicated BDS, the letter "a" – for applicable – shall be entered in the "test required" column against each of the tests indicated as being mandatory in the test schedule of the relevant sectional specification. Any additional test required at the discretion of the specification writer shall also be indicated by an "a".

The specification writer shall also indicate, when necessary, details of deviations from the standard test methods and test conditions, including any relevant deviations given in the test schedule of the sectional specification.

The qualification approval and conformance inspection shall be such that the National Supervising Inspectorate (NSI) shall be satisfied that they are appropriate and in line with those for other connectors within the system providing a reasonably comparable service.

IECNORM.COM : Click to view the full PDF of IEC 61169-35:2011

5.7 Blank detail specification pro forma for 2,92 series connectors

The following pages contain the complete BDS pro-forma.

| | | | |
|--|-------------------------------|---|------------------|
| (1) | | Page 1 of 10 | |
| | |  | |
| ELECTRONIC COMPONENT OF ASSESSED QUALITY IN ACCORDANCE WITH GENERIC SPECIFICATION IEC 61169-1 SECTIONAL SPECIFICATION IEC 61169-35 NATIONAL REFERENCE | | (4) ISSUE | |
| (5) Detail specification for Radio frequency coaxial connector of assessed quality | | | type 2,92 |
| Style:..... | | Special features and markings | |
| Method of cable/wire+ attachment | | centre conductor – solder/crimp+ outer conductor – solder/clamp/crimp + + delete as appropriate | |
| (6) Assessment level..... | Characteristic impedance 50 Ω | Climatic category...../...../...../ | |
| (7) Outline and maximum dimensions | | Panel piercing and mounting details | |
| (8) Variants | | | |
| Variant No. | Description of variant | 61196 IEC | |
| 01..... | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| Information about manufacturers who have components qualified to this detail specification is available through IECQ on-line certificate system. | | | |

(9) Performance (including limiting conditions of use)

| Ratings and characteristics | IEC 61169-1 Subclause | Value | Remarks including any deviations from standard test methods |
|--|-----------------------|--|---|
| <i>Electrical</i> | | | |
| Nominal impedance | | 50 Ω | |
| Frequency range | | 0 GHz - 18 GHz | Measurement frequency range |
| Reflection factor | 9.2.1 | | |
| Variant No. Designation 01..... | | | |
| Centre contact resistance | 9.2.3 | ≤mΩ ≤mΩ | Initial After conditioning |
| Centre conductor continuity 01..... | 9.2.4 |mΩmΩmΩmΩ | Resistance change due to conditioning |
| Outer contact continuity | 9.2.3 | ≤mΩ ≤mΩ | Initial After conditioning |
| Insulation resistance | 9.2.5 | ≥GΩ ≥GΩ | Initial After conditioning |
| #+ Proof voltage at sea level 01..... | 9.2.6 |kVkVkVkV | 86 kPa to 106 kPa |
| #+ Proof voltage at 4,4 kPa 01..... | |VVVV |kPa (if not 4,4 kPa) |
| #+ Environment test voltage at sea level 01..... | |VVVV | 86 kPa to 106 kPa |
| Environment test voltage at 4,4 kPa 01..... | |VVVV |kPa (if not 4,4 kPa) |
| <i>Electrical</i> | | | |
| Screening effectiveness 01..... | 9.2.8 | ≥ dB at...GHz | Z _c ≤.....Ω |
| ADDITIONAL ELECTRICAL CHARACTERISTICS | | | |

+ Voltage values are r.m.s. values at 50 Hz-60 Hz, unless otherwise specified.