

---

---

**Information technology — Generic coding  
of moving pictures and associated audio  
information: Systems**

**AMENDMENT 1: Transport of MPEG-4  
streaming text and MPEG-4 lossless audio  
over MPEG-2 systems**

*Technologies de l'information — Codage générique des images  
animées et des informations sonores associées: Systèmes*

*AMENDEMENT 1: Transport de texte en flux MPEG-4 et d'audio sans  
perte MPEG-4 sur des systèmes MPEG-2*

IECNORM.COM : Click to view the full text of ISO/IEC 13818-1:2007/Amd 1:2007

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

IECNORM.COM : Click to view the full PDF of ISO/IEC 13818-1:2007/Amd 1:2007



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/IEC 13818-1 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. H.222.0 (2006)/Amd.1 (01/2007).

IECNORM.COM : Click to view the full PDF of ISO/IEC 13818-1:2007/Amd 1:2007

INTERNATIONAL STANDARD  
ITU-T RECOMMENDATIONInformation technology – Generic coding of moving pictures  
and associated audio information: Systems

## Amendment 1

## Transport of MPEG-4 streaming text and MPEG-4 lossless audio over MPEG-2 systems

## 1) Subclause 1.2.3

Add the following references to subclause 1.2.3:

- ISO/IEC 14496-3:2005/Amd.1:2007, *Low delay AAC profile*.
- ISO/IEC 14496-17:2006, *Information technology – Coding of audio-visual objects – Part 17: Streaming text format*.

## 2) Subclause 2.1.1

Replace, in the definition for access unit in subclause 2.1.1:

In the case of audio, an access unit is the coded representation of an audio frame.

by:

In the case of audio, an access unit is the coded representation of an audio frame, whereby each audio frame carries data from one or more audio channels; an audio frame may carry for example one mono channel, or two stereo channels or seven surround sound channels.

In the case of an ISO/IEC 14496-17 text stream, see ISO/IEC 14496-17 for the definition of an access unit.

## 3) New subclause 2.4.2.9

Add, after subclause 2.4.2.8:

**2.4.2.9 T-STD extensions for carriage of ISO/IEC 14496-17 text streams**

To define the decoding in the T-STD of ISO/IEC 14496-17 text streams carried in a Transport Stream, the T-STD model needs to be extended. The T-STD extension and T-STD parameters for decoding of ISO/IEC 14496-17 text streams are defined in 2.15.3.1.

## 4) Subclause 2.4.3.5

Replace, in the semantics of "discontinuity indicator" under subclause 2.4.3.5 starting from the 5th paragraph:

For the purpose of this clause, an elementary stream access point is defined as follows:

- ISO/IEC 11172-2 video and ITU-T Rec. H.262 | ISO/IEC 13818-2 video – The first byte of a video sequence header.
- ISO/IEC 14496-2 visual – The first byte of the visual object sequence header.
- ITU-T Rec. H.264 | ISO/IEC 14496-10 video – The first byte of an AVC access unit. The SPS and PPS parameter sets referenced in this and all subsequent AVC access units in the coded video stream shall be provided after this access point in the byte stream and prior to their activation.
- Audio – The first byte of an audio frame.

by:

For the purpose of this clause, an elementary stream access point is defined as follows:

- ISO/IEC 11172-2 video and ITU-T Rec. H.262 | ISO/IEC 13818-2 video – The first byte of a video sequence header.
- ISO/IEC 14496-2 visual – The first byte of the visual object sequence header.
- ITU-T Rec. H.264 | ISO/IEC 14496-10 video – The first byte of an AVC access unit. The SPS and PPS parameter sets referenced in this and all subsequent AVC access units in the coded video stream shall be provided after this access point in the byte stream and prior to their activation.
- Audio – The first byte of an audio frame.
- ISO/IEC 14496-17 text stream – The first byte of a text access unit. In case in-band sample descriptions are used, each in-band sample description shall be provided in the ISO/IEC 14496-17 stream after this access point and prior to its use by an access unit.

5) **Subclause 2.4.3.7**

a) *In subclause 2.4.3.7, replace Table 2-27:*

**Table 2-27 – Stream\_id\_extension assignments**

stream_id_extension	Note	stream coding
000 0000	1	IPMP Control Information stream
000 0001	2	IPMP stream
000 0010 ... 011 1111		reserved_data_stream
100 0000 ... 111 1111		private_stream
NOTE 1 – PES packets of stream_id_extension 0b000 0000 (IPMP Control Information Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		
NOTE 2 – PES packets of stream_id_extension 0b000 0001 (IPMP Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		

by:

**Table 2-27 – Stream\_id\_extension assignments**

stream_id_extension	Note	stream coding
000 0000	1	IPMP Control Information stream
000 0001	2	IPMP stream
000 0010 ... 000 1111		ISO/IEC 14496-17 text stream
001 0000 ... 011 1111		reserved_data_stream
100 0000 ... 111 1111		private_stream
NOTE 1 – PES packets of stream_id_extension 0b000 0000 (IPMP Control Information Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		
NOTE 2 – PES packets of stream_id_extension 0b000 0001 (IPMP Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		

b) *Replace, in the semantics of PTS in subclause 2.4.3.7:*

The presentation time  $t_{pn}(k)$  shall be equal to the decoding time  $t_{dn}(k)$  for:

- audio access units;
- access units in ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 low delay video sequences;
- B-pictures in ISO/IEC 11172-2, ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 video streams.

by:

In the case of an ISO/IEC 14496-17 text stream, if a PTS is present in PES packet header, it shall refer to the first text access unit commencing in the PES packet. A text access unit commences in a PES packet if the first byte of the text access unit is present in the PES packet.

The presentation time  $t_{pn}(k)$  shall be equal to the decoding time  $t_{dn}(k)$  for:

- audio access units;
- access units in ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 low delay video sequences;
- B-pictures in ISO/IEC 11172-2, ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 video streams;
- text access units in ISO/IEC 14496-17.

## 6) Subclause 2.4.4.9

a) Replace Table 2-34 in subclause 2.4.4.9 with the following:

**Table 2-34 – Stream type assignments**

Value	Description
0x00	ITU-T   ISO/IEC Reserved
0x01	ISO/IEC 11172-2 Video
0x02	ITU-T Rec. H.262   ISO/IEC 13818-2 Video or ISO/IEC 11172-2 constrained parameter video stream
0x03	ISO/IEC 11172-3 Audio
0x04	ISO/IEC 13818-3 Audio
0x05	ITU-T Rec. H.222.0   ISO/IEC 13818-1 private_sections
0x06	ITU-T Rec. H.222.0   ISO/IEC 13818-1 PES packets containing private data
0x07	ISO/IEC 13522 MHEG
0x08	ITU-T Rec. H.222.0   ISO/IEC 13818-1 Annex A DSM-CC
0x09	ITU-T Rec. H.222.1
0x0A	ISO/IEC 13818-6 type A
0x0B	ISO/IEC 13818-6 type B
0x0C	ISO/IEC 13818-6 type C
0x0D	ISO/IEC 13818-6 type D
0x0E	ITU-T Rec. H.222.0   ISO/IEC 13818-1 auxiliary
0x0F	ISO/IEC 13818-7 Audio with ADTS transport syntax
0x10	ISO/IEC 14496-2 Visual
0x11	ISO/IEC 14496-3 Audio with the LATM transport syntax as defined in ISO/IEC 14496-3/Amd.1
0x12	ISO/IEC 14496-1 SL-packetized stream or FlexMux stream carried in PES packets
0x13	ISO/IEC 14496-1 SL-packetized stream or FlexMux stream carried in ISO/IEC 14496_sections
0x14	ISO/IEC 13818-6 Synchronized Download Protocol
0x15	Metadata carried in PES packets
0x16	Metadata carried in metadata_sections
0x17	Metadata carried in ISO/IEC 13818-6 Data Carousel
0x18	Metadata carried in ISO/IEC 13818-6 Object Carousel
0x19	Metadata carried in ISO/IEC 13818-6 Synchronized Download Protocol
0x1A	IPMP stream (defined in ISO/IEC 13818-11, MPEG-2 IPMP)
0x1B	AVC video stream as defined in ITU-T Rec. H.264   ISO/IEC 14496-10 Video
0x1C	ISO/IEC 14496-3 Audio, without using any additional transport syntax, such as DST, ALS and SLS
0x1D	ISO/IEC 14496-17 Text
0x1E-0x7E	ITU-T Rec. H.222.0   ISO/IEC 13818-1 Reserved
0x7F	IPMP stream
0x80-0xFF	User Private

b) Add below Table 2-34 the following clarifying text:

In the above table various stream types are assigned for carriage of audio signals, with or without a transport syntax. Typically, the transport syntax is used for providing sync words. The use of a specific transport syntax, if at all, is specified in the clauses in this Specification specifying the transport of the various audio signals.

## 7) Subclause 2.5.2.4

Replace, in subclause 2.5.2.4 "PES streams":

Buffer sizes  $BS_n$  in the PES-STD model are defined as follows:

- For ITU-T Rec. H.262 | ISO/IEC 13818-2 video:

$$BS_n = VBV_{\max}[\text{profile, level}] + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}[\text{profile, level}]$ , where  $VBV_{\max}[\text{profile, level}]$  and  $R_{\max}[\text{profile, level}]$  are the maximum VBV size and bit rate per profile, level, and layer as defined in Tables 8-13 and 8-14, respectively, of ITU-T Rec. H.262 | ISO/IEC 13818-2.  $BS_{\text{oh}}$  is allocated for PES packet header overhead.

- For ISO/IEC 11172-2 video:

$$BS_n = VBV_{\max} + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}$ , where  $R_{\max}$  and  $vbv_{\max}$  refer to the maximum bitrate and maximum  $vbv\_buffer\_size$  for a constrained parameter bitstream in ISO/IEC 11172-2 respectively.

- For ISO/IEC 11172-3 or ISO/IEC 13818-3 audio:

$$BS_n = 2848 \text{ bytes}$$

- For ITU-T Rec. H.264 | ISO/IEC 14496-10 video:

$$BS_n = 1200 \times \text{MaxCPB}[\text{level}] + BS_{\text{oh}}$$

where  $\text{MaxCPB}[\text{level}]$  is defined in Table A.1 (Level Limits) in ITU-T Rec. H.264 | ISO/IEC 14496-10 for each level.

by:

As a PES stream only carries a single elementary stream, the buffer sizes in the PES-STD do not account for multiplexing with other elementary streams, but only for multiplexing of the elementary stream carried in the PES stream with PES headers, pack headers and system headers. The buffer sizes  $BS_n$  in the PES-STD model are defined as follows:

- For ITU-T Rec. H.262 | ISO/IEC 13818-2 video:

$$BS_n = VBV_{\max}[\text{profile, level}] + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}[\text{profile, level}]$ , where  $VBV_{\max}[\text{profile, level}]$  and  $R_{\max}[\text{profile, level}]$  are the maximum VBV size and bit rate per profile, level, and layer as defined in Tables 8-13 and 8-14, respectively, of ITU-T Rec. H.262 | ISO/IEC 13818-2.  $BS_{\text{oh}}$  is allocated for PES packet header overhead.

- For ISO/IEC 11172-2 video:

$$BS_n = VBV_{\max} + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}$ , where  $R_{\max}$  and  $vbv_{\max}$  refer to the maximum bitrate and maximum  $vbv\_buffer\_size$  for a constrained parameter bitstream in ISO/IEC 11172-2 respectively.

- For ISO/IEC 11172-3 or ISO/IEC 13818-3 audio:

$$BS_n = 2848 \text{ bytes}$$

- For ISO/IEC 13818-7 ADTS audio:

$BS_n = 2848$  bytes if 1-2 channels  
 $BS_n = 7200$  bytes if 3-8 channels  
 $BS_n = 10800$  bytes if 9-12 channels  
 $BS_n = 43200$  bytes if 13-48 channels

Note that the above numbers differ from the  $BS_n$  numbers specified in 2.4.3.2 due to the fact that a PES stream carries a single elementary stream only.

- For ISO/IEC 14496-3 audio, except for ISO/IEC 14496-3 DST, ALS and SLS:

$BS_n = 2848$  bytes if 1-2 channels  
 $BS_n = 7200$  bytes if 3-8 channels  
 $BS_n = 10800$  bytes if 9-12 channels  
 $BS_n = 43200$  bytes if 13-48 channels

Note that the above numbers differ from the  $BS_n$  numbers specified in 2.11.2.2 due to the fact that a PES stream carries a single elementary stream only.

- For ISO/IEC 14496-3 DST-64 audio:

$BS_n = 5000 \times (\text{number of channels})$  bytes; hence for stereo  $BS_n = 10\,000$  bytes  
 and for 5.1 surround sound audio  $BS_n = 30\,000$  bytes

- For ISO/IEC 14496-3 DST-128 audio:

$BS_n = 10\,000 \times (\text{number of channels})$  bytes; hence for stereo  $BS_n = 20\,000$  bytes  
 and for 5.1 surround sound audio  $BS_n = 60\,000$  bytes

- For ISO/IEC 14496-3 DST-256 audio:

$BS_n = 20\,000 \times (\text{number of channels})$  bytes; hence for stereo  $BS_n = 40\,000$  bytes  
 and for 5.1 surround sound audio  $BS_n = 120\,000$  bytes

- For ISO/IEC 14496-3 ALS and SLS audio:

$BS_n = 33\,000 \times (\text{number of channels})$  bytes; hence for stereo  $BS_n = 66\,000$  bytes  
 and for 5.1 surround sound audio  $BS_n = 198\,000$  bytes

- For ITU-T Rec. H.264 | ISO/IEC 14496-10 video:

$$BS_n = 1200 \times \text{MaxCPB}[\text{level}] + BS_{oh}$$

where  $\text{MaxCPB}[\text{level}]$  is defined in Table A.1 (Level Limits) in ITU-T Rec. H.264 | ISO/IEC 14496-10 for each level.

## 8) New subclause 2.5.2.8

Add, after subclause 2.5.2.7:

### 2.5.2.8 P-STD extensions for carriage of ISO/IEC 14496-17 text streams

For decoding of ISO/IEC 14496-17 text streams carried in a Program Stream in the P-STD model, see 2.15.3.2.

## 9) Subclause 2.6.1

Replace Table 2-45 with the following one:

Table 2-45 – Program and program element descriptors

descriptor_tag	TS	PS	Identification
0	n/a	n/a	Reserved
1	n/a	n/a	Reserved
2	X	X	video_stream_descriptor
3	X	X	audio_stream_descriptor
4	X	X	hierarchy_descriptor
5	X	X	registration_descriptor
6	X	X	data_stream_alignment_descriptor
7	X	X	target_background_grid_descriptor
8	X	X	video_window_descriptor
9	X	X	CA_descriptor
10	X	X	ISO_639_language_descriptor
11	X	X	system_clock_descriptor
12	X	X	multiplex_buffer_utilization_descriptor
13	X	X	copyright_descriptor
14	X		maximum_bitrate_descriptor
15	X	X	private_data_indicator_descriptor
16	X	X	smoothing_buffer_descriptor
17	X		STD_descriptor
18	X	X	IBP_descriptor
19-26	X		Defined in ISO/IEC 13818-6
27	X	X	MPEG-4_video_descriptor
28	X	X	MPEG-4_audio_descriptor
29	X	X	IOD_descriptor
30	X		SL_descriptor
31	X	X	FMC_descriptor
32	X	X	external_ES_ID_descriptor
33	X	X	MuxCode_descriptor
34	X	X	FmxBufferSize_descriptor
35	X		multiplexbuffer_descriptor
36	X	X	content_labeling_descriptor
37	X	X	metadata_pointer_descriptor
38	X	X	metadata_descriptor
39	X	X	metadata_STD_descriptor
40	X	X	AVC video descriptor
41	X	X	IPMP_descriptor (defined in ISO/IEC 13818-11, MPEG-2 IPMP)
42	X	X	AVC timing and HRD descriptor
43	X	X	MPEG-2 AAC audio descriptor
44	X	X	FlexMux_Timing_descriptor
45	X	X	MPEG-4_text_descriptor
46	X	X	MPEG-4_audio_extension_descriptor
47-63	n/a	n/a	ITU-T Rec. H.222.0   ISO/IEC 13818-1 Reserved
64-255	n/a	n/a	User Private

**10) Subclause 2.6.39**

Replace, in subclause 2.6.39:

**MPEG-4\_audio\_profile\_and\_level** – This 8-bit field shall identify the profile and level of the ISO/IEC 14496-3 audio stream corresponding to the Table 2-71.

by:

**MPEG-4\_audio\_profile\_and\_level** – This 8-bit field identifies the profile and level of the ISO/IEC 14496-3 audio stream corresponding to Table 2-71. If encoded with the value 0x0F, then it is signalled that no profile and level is defined for the associated MPEG-4 audio stream. The encoded value 0xFF indicates that the audio profile and level is not specified by the MPEG-4\_audio\_profile\_and\_level field; in that case, in addition to the MPEG-4 audio descriptor, an MPEG-4 audio extension descriptor shall be associated to the same MPEG-4 audio stream. In all other cases, next to an MPEG-4 audio descriptor, also an MPEG-4 audio extension descriptor may be associated to the same MPEG-4 audio stream.

**11) Subclause 2.6.39**

Replace Table 2-71 by the following table:

**Table 2-71 – MPEG-4\_audio\_profile\_and\_level assignment values**

Value	Description
0x00-0x0E 0x0F	Reserved No audio profile and level defined for the associated MPEG-4 audio stream
0x10 0x11 0x12 0x13 0x14-0x17	Main profile, level 1 Main profile, level 2 Main profile, level 3 Main profile, level 4 Reserved
0x18 0x19 0x1A 0x1B 0x1C-0x1F	Scalable Profile, level 1 Scalable Profile, level 2 Scalable Profile, level 3 Scalable Profile, level 4 Reserved
0x20 0x21 0x22-0x27	Speech profile, level 1 Speech profile, level 2 Reserved
0x28 0x29 0x2A 0x2B-0x2F	Synthesis profile, level 1 Synthesis profile, level 2 Synthesis profile, level 3 Reserved
0x30 0x31 0x32 0x33 0x34 0x35 0x36 0x37	High quality audio profile, level 1 High quality audio profile, level 2 High quality audio profile, level 3 High quality audio profile, level 4 High quality audio profile, level 5 High quality audio profile, level 6 High quality audio profile, level 7 High quality audio profile, level 8
0x38 0x39 0x3A 0x3B 0x3C	Low delay audio profile, level 1 Low delay audio profile, level 2 Low delay audio profile, level 3 Low delay audio profile, level 4 Low delay audio profile, level 5

Table 2-71 – MPEG-4\_audio\_profile\_and\_level assignment values

Value	Description
0x3D	Low delay audio profile, level 6
0x3E	Low delay audio profile, level 7
0x3F	Low delay audio profile, level 8
0x40	Natural audio profile, level 1
0x41	Natural audio profile, level 2
0x42	Natural audio profile, level 3
0x43	Natural audio profile, level 4
0x44-0x47	Reserved
0x48	Mobile audio internetworking profile, level 1
0x49	Mobile audio internetworking profile, level 2
0x4A	Mobile audio internetworking profile, level 3
0x4B	Mobile audio internetworking profile, level 4
0x4C	Mobile audio internetworking profile, level 5
0x4D	Mobile audio internetworking profile, level 6
0x4E-0x4F	Reserved
0x50	AAC profile, level 1
0x51	AAC profile, level 2
0x52	AAC profile, level 4
0x53	AAC profile, level 5
0x54-0x57	Reserved
0x58	High efficiency AAC profile, level 2
0x59	High efficiency AAC profile, level 3
0x5A	High efficiency AAC profile, level 4
0x5B	High efficiency AAC profile, level 5
0x5C-0x5F	Reserved
0x60	High efficiency AAC v2 profile, level 2
0x61	High efficiency AAC v2 profile, level 3
0x62	High efficiency AAC v2 profile, level 4
0x63	High efficiency AAC v2 profile, level 5
0x64-0xFE	Reserved
0xFF	Audio profile and level not specified by the MPEG-4_audio_profile_and_level field in this descriptor

## 12) New subclauses 2.6.70 to 2.6.73

Add, after subclause 2.6.69:

### 2.6.70 MPEG-4 text descriptor

The MPEG-4 text descriptor carries textConfig() specified in ISO/IEC 14496-17 for the associated ISO/IEC 14496-17 text stream, thereby providing basic information needed for the decoding of the associated ISO/IEC 14496-17 stream. For each ISO/IEC 14496-17 text stream carried in an ITU-T Rec. H.222.0 | ISO/IEC 13818-1 stream, the MPEG-4 text descriptor shall be included in the PMT or in the PSM, if PSM is present in the program stream.

Table 2-92.1 – MPEG-4 text descriptor

Syntax	No. of bits	Mnemonic
<pre>MPEG-4_text_descriptor () {   descriptor_tag   descriptor_length   textConfig() }</pre>	<p>8</p> <p>8</p>	<p>uimsbf</p> <p>uimsbf</p>

### 2.6.71 Semantic definition of fields in MPEG-4 text descriptor

**textConfig()** – This shall carry the TextConfig() of the associated ISO/IEC 14496-17 text stream, as defined in ISO/IEC 14496-17.

### 2.6.72 MPEG-4 audio extension descriptor

The MPEG-4 audio extension descriptor carries zero or more audioProfileLevelIndication fields and zero or one audioSpecificConfig() field, both encoded as specified in ISO/IEC 14496-3. Note that for each ISO/IEC 14496-3 audio stream carried in an ITU-T Rec. H.222.0 | ISO/IEC 13818-1 stream, it is required that the MPEG-4 audio descriptor be included in the PMT or in the PSM, if PSM is present in the program stream, while the MPEG-4 audio extension descriptor may be present too, providing additional information. If in the MPEG-4 audio descriptor the MPEG-4\_audio\_profile\_and\_level field is encoded with the value 0xFF, indicating that the audio profile and level is not specified in the MPEG-4 audio descriptor, then the MPEG-4 audio extension descriptor shall be present in the same PMT or PSM as the MPEG-4 audio descriptor. Note that this descriptor allows to provide the audioSpecificConfig out of band, so as to allow receivers to retrieve information about the associated audio stream without accessing the stream itself. The descriptor also allows to associate an audioSpecificConfig to an audio stream.

Table 2-92.2 – MPEG-4 audio extension descriptor

Syntax	No. of bits	Mnemonic
<pre>MPEG-4_audio_extension_descriptor () {   descriptor_tag   descriptor_length   ASC_flag   reserved   num_of_loops   for (i=0; i&lt;num_of_loops; i++) {     audioProfileLevelIndication   }   if (ASC_flag == '1') {     ASC_size     audioSpecificConfig()   } }</pre>	<p>8</p> <p>8</p> <p>1</p> <p>3</p> <p>4</p> <p>8</p> <p>8</p>	<p>uimsbf</p> <p>uimsbf</p> <p>bslbf</p> <p>bslbf</p> <p>uimsbf</p> <p>uimsbf</p> <p>uimsbf</p>

### 2.6.73 Semantic definition of fields in MPEG-4 audio extension descriptor

**ASC\_flag** – A one-bit flag signalling the presence of the ASC\_size field in this descriptor.

**num\_of\_loops** – A 4-bit field specifying the number of immediately following audioprofileLevelIndication fields in this descriptor. This field may be encoded with the value zero.

**audioProfileLevelIndication** – The audio profile and level of the associated ISO/IEC 14496-3 audio stream, encoded as specified for the audioprofileLevelIndication field in subclause 1.5.2.1 in ISO/IEC 14496-3. Note that a single ISO/IEC 14496-3 audio stream may comply to more than one audio profile and level, and that this descriptor is designed to convey up to 15 different audioprofileLevelIndication values.

**ASC\_size** – The number of bytes of the immediately following AudioSpecificConfig().

**audioSpecificConfig()** – The audioSpecificConfig() of the associated ISO/IEC 14496-3 audio stream, as specified in subclause 1.6.2.1 in ISO/IEC 14496-3.

**13) Subclause 2.11.1**

Add the following paragraph at the end of subclause 2.11.1:

Carriage of ISO/IEC 14496-17 text streams over ITU-T Rec. H.222.0 | ISO/IEC 13818-1 streams is specified in 2.15.

**14) Subclause 2.11.2.1**

a) *Replace, in subclause 2.11.2.1:*

In case of an ISO/IEC 14496-3 elementary stream, before PES packetization the elementary stream data shall be first encapsulated in the LATM/LOAS AudioSyncStream() transport syntax defined in ISO/IEC 14496-3. If a PTS is present in the PES packet header, it shall refer to the first audio frame that follows the first syncword that commences in the payload of the PES packet.

*by:*

In case of an ISO/IEC 14496-3 elementary stream signalled by a stream\_type value of 0x11, before PES packetization the elementary stream data shall be first encapsulated in the LATM transport syntax defined in ISO/IEC 14496-3. In such case, If a PTS is present in the PES packet header it shall refer to the first audio frame that follows the first syncword that commences in the payload of the PES packet.

In case of an ISO/IEC 14496-3 elementary stream signalled by a stream\_type value of 0x1C, the first byte of each audio frame shall be the first byte of the payload of a PES packet; prior to PES packetization no encapsulation in any additional transport syntax shall be applied. An audio frame from an ISO/IEC 14496-3 elementary stream signalled by a stream\_type value of 0x1C may be fragmented for carriage in multiple PES packets. In the PES packet header the data\_alignment\_indicator shall be set to '1' in each PES packet that carries a complete such audio frame or the first fragment thereof. The data\_alignment\_indicator shall be set to '0' for PES packets carrying subsequent (non-first) fragments of an audio frame.

b) *Add, after the last paragraph of subclause 2.11.2.1:*

Carriage of an individual ISO/IEC 14496-17 text streams in PES packets shall be identified by appropriate stream\_id and stream\_type values, indicating the use of ISO/IEC 14496-17 text.

**15) Subclause 2.11.2.2**

*Replace, in subclause 2.11.2.2:*

In case of carriage of an ISO/IEC 14496-3 stream:

Size  $BS_n$  of Buffer  $B_n$  for ISO/IEC 14496-3 AAC audio,

else  $BS_n = BS_{mux} + BS_{dec} + BS_{oh} = 3584$  bytes

In this case the size of the access unit decoding buffer  $BS_{dec}$ , and the PES packet overhead buffer  $BS_{oh}$  are constrained by:

$$BS_{dec} + BS_{oh} \leq 2848 \text{ bytes}$$

A portion (736 bytes) of the 3584 byte buffer is allocated for buffering to allow multiplexing. The rest, 2848 bytes, are shared for access unit buffering  $BS_{dec}$ ,  $BS_{oh}$  and additional multiplexing.

Rate  $R_{x_n}$  for ISO/IEC 14496-3 AAC audio same as defined for ISO/IEC 13818-7 ADTS audio in 2.4.2.3,

else  $R_{x_n} = 2\ 000\ 000$  bit/s