

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-39029/13A(AS) AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-39029/13A(AS). ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.


UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

**AS39029/13**

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."  
SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

SAENORM.COM : Click to view the full PDF of as39029 - 13

THIRD ANGLE PROJECTION



ISSUED 2000-06

PREPARED BY SAE SUBCOMMITTEE AE-8C1



**AEROSPACE STANDARD**


CONTACTS, ELECTRICAL CONNECTOR,  
SOCKET, CRIMP REMOVABLE, SHIELDED,  
(FOR MIL-C-81511 SERIES 1 CONNECTORS)

**AS39029/13**  
SHEET 1 OF 7

THE COMPLETE REQUIREMENTS FOR PROCURING THE CONTACTS DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF SPECIFICATION MIL-C-39029.

INACTIVE FOR NEW DESIGN

AS39029/13



NOTES:

1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Metric equivalents are in parentheses for overall length and diameter only.
4. Dimensions shown apply after plating.

FIGURE 1. CONNECTOR CONTACT.

TABLE I. DIMENSIONS.

BIN code	A DIA	B DIA	C DIA	D DIA	E MAX DIA	AA DIA	BB MIN DIA	CC DIA	DD DIA	EE DIA	FF MIN DIA	HH MIN DIA	HHH MAX DIA	U
152	.103 .101	.0910 .0885	.113 .110	.0750 .0725	.042	.081 .078	.022	.133 (3.38) .130 (3.30)	.099 .096	.068 .062	.037	.058	.087	.042 .018
153	.162 .159	.1430 .1405	.161 .158	.1210 .1175	.070	.128 .126	.022	.190 (4.83) .187 (4.75)	.145 .142	.076 .070	.067	.086	.130	.042 .018
154	.162 .159	.1430 .1405	.161 .158	.1210 .1175	.070	.128 .126	.022	.190 (4.83) .187 (4.75)	.145 .142	.076 .070	.093	.110	.130	.042 .018
155	.162 .159	.1430 .1405	.161 .158	.1210 .1175	.070	.128 .126	.022	.190 (4.83) .187 (4.75)	.145 .142	.076 .070	.108	.128	.142	.042 .018
156	.162 .159	.1430 .1405	.161 .158	.1210 .1175	.070	.128 .126	.034	.190 (4.83) .187 (4.75)	.145 .142	.089 .085	.098	.128	.142	.042 .018
157	.162 .159	.1430 .1405	.161 .158	.1210 .1175	.070	.128 .126	.034	.190 (4.83) .187 (4.75)	.145 .142	.089 .085	.098	.110	.130	.042 .018




FIGURE 2. ASSEMBLY PROCEDURE.

AS39029/13

TABLE II. DESIGN CHARACTERISTICS.

BIN code	Color bands			Contact cavity size	Cable <sup>c</sup> accommodated	Type	Class
	1st	2nd	3rd				
152	Brown	Green	Red	16	RG-178A/U RG-196A/U	D	B
153	Brown	Green	Orange	12	RG-179B/U RG-187A/U RG-188A/U		
154	Brown	Green	Yellow	12	9530D5117 (RAYCHEM) <u>1/</u>		
155	Brown	Green	Green	12	RG-180B/U RG-195A/U 293-3922 (MICRODOT) <u>1/</u>		
156	Brown	Green	Blue	12	250-4070 (MICRODOT) <u>1/</u>		
157	Brown	Green	Violet	12	5022E5111 (RAYCHEM) <u>1/</u>		

1/ or equivalent

REQUIREMENTS:

Dimensions, design characteristics, and configuration: See figure 1 and tables I and II.

Tools: See table III.

Mating contact: MIL-C-39029/6.

Manufacturer's recommended assembly instruction to be shipped with unit package.

Assembly procedure: See figure 2.

Preparation of samples: Contacts shall be wired as required using wire in accordance with table II (cables accommodated column).

Contact resistance: Contact resistance at a load current of 1.0 ampere shall meet the requirements of table IV.

Contact engagement and separation forces: The contact separation and engagement forces shall meet the requirements of table IV.

Dielectric withstanding voltage: 1,000 volts, ac, rms from sea level to 110,000 feet altitude.

Tensile strength: The tensile strength shall meet the requirements of table IV.

QPL evaluating activity: Naval Weapons Support Center, Code 3074, Crane, Indiana 47522.