

Issued 1989-10  
Revised 1998-07  
Stabilized 2012-12

Superseded by ARP4156

**Color-Coded Incandescent Flange Base  
T-1 and T-1 3/4 Lamps for Voltage Identification**

**RATIONALE**

This document has been determined to contain basic and stable technology which is not dynamic in nature. This document has been superseded by ARP4156 due to the material herein not being significant to be a current Aerospace Standard.

**STABILIZED NOTICE**

This document has been declared "Stabilized" by the SAE A-20A Crew Station Lighting Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of AS4156b

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2012 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
Tel: +1 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: CustomerService@sae.org  
**SAE WEB ADDRESS:** <http://www.sae.org>

**SAE values your input. To provide feedback  
on this Technical Report, please visit  
<http://www.sae.org/technical/standards/AS4156B>**

## FOREWORD

There are a number of incandescent flange base miniature lamps that have identical appearance and produce approximately the same light output, but are designed at different voltages, primarily, 5.0, 14.0, 28.0, and 32.0 volts. In several applications, a 5.0 volt lamp installed in place of a 28.0 volt lamp can cause failures of electronic components due to its lower impedance and, consequently, higher current. Because these lamps are identical in appearance and so small as to make identification by markings almost impossible, this document is intended to provide a means of identification of voltage differences.

### 1. SCOPE:

This document defines the method for voltage identification by the use of color-coded insulators at the base of the lamp. Table 1 shows the design volts and corresponding insulator colors.

The part numbers shown are for example purposes only.

Insulator colors are to be easily distinguishable as green, yellow, red, and white. Additional colors may be added by a revision process as required.

### 2. REFERENCES:

There are no referenced publications specified herein.

### 3. RECOMMENDATIONS:

For aerospace applications, lamps should be ordered by the part numbers as shown in the examples in Table 1 so that replacement lamps can be easily identified as to voltage.